


M158BB9

Monocrystalline Bifacial Cells

Dimension	158.75mm x 158.75mm ± 0.25mm
Thickness(Si)	190μm ± 30μm
Front	9*0.1mm main grid lines (silver)
	114 sub grid lines
Back	blue anti-reflection film (Silicon Nitride)
	Back electrode width (Silver) 1.8mm, backside covered with aluminum back field





► Features

- > High conversion efficiencies resulting in superior power output performance
- > Outstanding power output even in low light or high temperature conditions
- > Optimized design for ease of soldering and lamination
- > Long-term stability, reliability and performance
- > Low breakage rate
- > Uniform Color

► Production and Quality Control

- > Precision cell efficiency sorting procedures
- > Stringent criteria for color uniformity and appearance
- > Reverse current and shunt resistance screening
- > ISO9001, ISO14001 and OHSAS 18001 certificated
- > Calibrated against Fraunhofer ISE



*See the reverse side for more detail.

Sunlike Solar Co.,Ltd

No.509, Datong Road, Wuxi, Jiangsu, China

Tel: 0086-510-88990686

Email: solar@sunlikesolar.com

Website: <http://www.sunlikesolar.com>

M158BB9

► Electrical Performance

Efficiency Code		22.2	22.1	22.0	21.9	21.8	21.7
Efficiency	Eff(%)	22.20	22.10	22.00	21.90	21.80	21.70
Power	Ppm(W)	5.59	5.57	5.54	5.52	5.49	5.47
Max. Power Current	Ipm(A)	9.78	9.76	9.74	9.73	9.71	9.70
Short Circuit Current	Isc(A)	10.32	10.31	10.29	10.28	10.27	10.25
Max. Power Voltage	Vpm(V)	0.578	0.577	0.576	0.574	0.573	0.570
Open Circuit Voltage	Voc(V)	0.682	0.681	0.680	0.679	0.677	0.675
Efficiency Code		21.6	21.5	21.4	21.3	21.1	
Efficiency	Eff(%)	21.60	21.50	21.40	21.30	21.10	
Power	Ppm(W)	5.44	5.42	5.39	5.37	5.32	
Max. Power Current	Ipm(A)	9.70	9.69	9.68	9.67	9.67	
Short Circuit Current	Isc(A)	10.24	10.24	10.22	10.21	10.21	
Max. Power Voltage	Vpm(V)	0.568	0.566	0.563	0.560	0.557	
Open Circuit Voltage	Voc(V)	0.673	0.672	0.668	0.665	0.662	


Standard test condition :AM1.5,1000W/m², 25°C

Average accuracy of all tested figures is ± 1.5% rel.


► Temperature Coefficients

Current Temperature Coefficient	$\alpha(I_{sc})$	0.06%/°C
Voltage Temperature Coefficient	$\beta(V_{oc})$	-0.36%/°C
Power Temperature Coefficient	$\gamma(P_{max})$	-0.36%/°C

► IV Curve



► Spectral Response(SR)



Specifications subject to change without prior notice.
SUNLIKE reserves the rights of final interpretation and revision of this datasheet.

Sunlike Solar Co.,Ltd

No.509, Datong Road, Wuxi, Jiangsu, China

Tel: 0086-510-88990686

Email: solar@sunlikesolar.com

Website: <http://www.sunlikesolar.com>