

SERIES MODELS


MPPT Solar Charger Controller	Sunwins MC-30F	Sunwins MC-30N	Sunwins MC-40F	Sunwins MC-40N
	Sunwins MC-50F	Sunwins MC-50N	Sunwins MC-60F	Sunwins MC-60N
	Sunwins MC-70F	Sunwins MC-70N	Sunwins MC-80F	Sunwins MC-80N

PRODUCT FEATURES



- Flexible for 12/24/48V System
- Fan cooling
- Advanced MPPT Technology 99%
- Multiphase synchronous rectification technology
- Peak conversion efficiency of 98%
- Nominal maximum solar input is DC 150V
- Multifunction LCD displays system data and status
- Three stages charging optimizes battery performance
- PV array short circuit Protection
- PV over current Protection
- PV over voltage Protection
- PV reverse polarity Protection
- Battery reverse polarity Protection
- Over charging Protection
- Overheating protection

BLOCK DIAGRAM



PRODUCT CERTIFICATION



PART V / SOLAR CHARGER CONTROLLER SUNWINS MC SERIES II



TECHNICAL DATA

	Sunwins MC-50F	Sunwins MC-60F	Sunwins MC-50N	Sunwins MC-60N
ELECTRICAL				
Solar system voltage	12V / 24V / 48V Flexible			
PV Operating Voltage	17~150 VDC@12V / 34~150VDC@24V / 60~150VDC@48V			
Maximum PV Open Circuit Voltage	150VDC			
Maximum PV Input Power	12V 700W	12V 800W	12V 700W	12V 800W
	24V 1400W	24V 1700W	24V 1400W	24V 1700W
	48V 2800W	48V 3400W	48V 2800W	48V 3400W
Maximum Charging Current	50 A	60 A	50 A	60 A
Self Consumption	4W		3W	
Conversion Efficiency	97.8%		98%	
Protection	Overload, Short circuit, High voltage, High temperature, Protection			
BATTERY				
Connected Battery Type	Sealed AGM Gel Flooded			
Charging Algorithm	3-stage: Bulk, Absorption, Float		4-stage: Bulk, Absorption, Float, Equalize	
Bulk Charge Voltage	Sealed: 14.4V AGM Gel:14.2V Flooded:14.6V Custom:10-17V			
Float Charge Voltage	Sealed / Gel / AGM : 13.7V Flood:13.6V Custom:10-17V			
Equalize Charge Voltage	Sealed:14.6V AGM:14.8V Flooded:14.9V Custom:10-17V			
Low Voltage Reconnect Voltage	10.2 V			
Low Voltage Disconnect Voltage	9V			
Temperature Compensation	-5mV / °C / 2V with BTS			
COMMUNICATION				
Communication Port	Standard Rs485 / 232 / Ethernet Communication		Standard Rs485 / 232 / Ethernet On line monitor system	
PHYSICAL				
Net Weight	3 kg		5.6 kg	
Gross Weight	4 kg		6.1 kg	
Dimension,W x H x D	280*180*89 mm		297*227*110 mm	
Cooling	Fan cooling		Heatsink cooling	
Protection Degree	IP 21		IP 54	
ENVIRONMENT				
Relative Humidity	100% non-condensing			
Operating Temperature	-25°C to 60°C (Derating from 45°C)			
Storage Temperature	-40°C to 80°C			
Standard Warranty(years)	2 years			


* Product specifications are subject to change without further notice

Version : 2.0


PACKING SIZES



Product Size



Product Packing Size




Standard Pallet Size




Pallet Packing Model

COLOR OPTIONS



DIFFERENT WORKING MODE



SYSTEM SOLUTION & APPLICATION CASES



We can provide :

- * 1kw to 200kw on-grid / off-grid / storage energy solutions.
- * Professional design and good quality.
- * Ensure safe and convenient construction.
- * Easy to maintain and convenient to replace.
- * Wide applications range for different environments.

Sunwins Technologies (Suzhou) Co.,Ltd.

5F, Building 2, No.2358, Changan RD, Suzhou, 215200, P.R.CHINA

TEL: +86 512 6316 9621 FAX: +86 512 6316 9571

WEB: www.sunwins-tech.com

E-MAIL: Info@sunwins-tech.com / sales@sunwins-tech.com

