



Model: PC1500B-60DU

### PC1500B Series PWM Solar Charge Controller


#### Feature:

- 10A 20A 30A 50A 60A solar charge controller
- Vivid LCD graphic symbols
- Simple button operation
- Automatic identification of system voltage level
- Intelligent PWM charging mode
- Adjustable charge-discharge protection
- Automatic temperature compensation
- Settable operation mode of load
- Battery reverse-discharge protection
- Battery low voltage disconnection(LVD)
- Battery reverse connection protection
- Over current protection
- USB output

#### Introduction:


This intelligent, multi-purpose solar charge and discharge controller has a very friendly interface of fixed LCD display. Various control parameters can be flexibly set, fully meet your various application requirements.

#### LCD Display Information



1. PV array positive terminal
2. PV array negative terminal
3. Battery positive terminal
4. Battery negative terminal
5. The load positive terminal
6. The load negative terminal
7. LCD display

#### Solar System Connection




#### Functions:



#### Inner Details



Stability, high efficiency, high integration



Optimized circuit design



SCM accurate control



Selection of quality materials

### PC1500B SERIES Controllers



Model: PC1500B-20DU



Rated Voltage: 12V24V Auto identified  
Rated Current: 20A  
USB Port: 5V, 1A x 2

Packing info: 30pcs / carton  
Carton size: 535mm x 425mm x 200mm  
Gross weight: 12Kg  
Volume: 0.045m³



Model: PC1500B-30DU



Rated Voltage: 12V24V Auto identified  
Rated Current: 30A  
USB Port: 5V, 1A x 2  
LCD screen size: 2.2"

Packing info: 30pcs / carton  
Carton size: 535mm x 425mm x 200mm  
Gross weight: 12Kg  
Volume: 0.045m³



Model: PC1500B-50D / 5048D

Rated Voltage: 12V24V Auto identified or 48V  
Rated Current: 40A, 50A

LCD screen size: 2.6"  
Temperature sensor port: x1  
Communication port: RJ45 ( Optional )

Packing info: 24pcs / carton  
Carton size: 545mm x 425mm x 205mm  
Gross weight: 14Kg  
Volume: 0.047m³



Model: PC1500B-60D / 6048D

Rated Voltage: 12V24V Auto identified or 48V  
Rated Current: 60A

LCD screen size: 2.6"  
Temperature sensor port: x1  
Communication port: RJ45 ( Optional )

Packing info: 24pcs / carton  
Carton size: 545mm x 425mm x 205mm  
Gross weight: 17Kg  
Volume: 0.047m³

#### Application



RV, boat & field power supply solar system



Off-grid home solar system



Farm solar generation system

	Model	PC1500B-50D		PC1500B-60DU		PC1500B-5048D		PC1500B-6048D	
INPUT	PV voltage			≤50V				≤100V	
	Rated current	40A	50A	60A		40A	50A	60A	
	System voltage			12/24V Auto				48V	
	High voltage disconnection			16.00V x 1 / x 2 / x 3 / x 4 ( 0.5V )					
	Rated discharging current	40A	50A	60A		40A	50A	60A	
	No load loss			≤13mA				≤25mA	
	Charge loop voltage drop	≤0.21V		≤0.24V		≤0.25V		≤0.25V	
	Discharge loop voltage drop	≤0.12V		≤0.10V		≤0.12V		≤0.10V	
OUTPUT	Charging mode			PWM 4-stage bulk, absorption, float, equalized					
	Float charging voltage			13.8V (13V~15V) x 1 / x 2 / x 3 / x 4					
	Absorption charging voltage			14.4V (13V~15V) x 1 / x 2 / x 3 / x 4					
	Equalized charging voltage			Duration 2 hours		14.6V (13V~15.5V) x 1 / x 2 / x 3 / x 4			
	Low voltage protection			10.7V (10V~14V) x 1 / x 2 / x 3 / x 4					
	Low voltage reconnecting			12.6V (10V~14V) x 1 / x 2 / x 3 / x 4					
	USB output	5V, 1A				None			
OTHER	Installing cables size	≤6mm²	≤16mm²	≤6mm²	≤16mm²				
	Working temperature			-20°C~55°C					
	Dimention(L x W x H)			188mm x 95mm x 46.5mm					
	Net weight	355g	360g	355g	360g				

\* Product specifications are subject to change without further notice.