

SC-05SM/SM-Z~SC-20SM/SM-Z

Solar Charger

For a variety of load applications, SC-SM and SC-SM-Z series offer you options.

SC-SM series with a PV sensor can output or not depending on PV power of levels, whereas SC-SM-Z series can continuously output whatever PV power exists or not.

Features

- 12V/24V automatic recognition
- Automatic temperature compensation
- Three-stage charge method
- Electronic protections
- IP68 enclosure

IP68
Dustproof & Waterproof



Application diagram



Specifications

Model	SC-05SM/SM-Z	SC-10SM/SM-Z	SC-15SM/SM-Z	SC-20SM/SM-Z
Nominal voltage	12 V / 24 V automatic recognition			
Max solar current or load current	5A	10A	15A	20A
Boost voltage	14.5 / 29 V (25°C)			
Equalization voltage	14.8 / 29.6 V (25°C)			
Float voltage	13.7 / 27.4 V (25°C)			
Battery type	Flooded, Sealed			
Max solar voltage	55V			
Max battery voltage	40V			
Cable length	120mm / 80mm			
Over voltage protection	15.5 V / 31.0 V			
Dimensions / Weight	85 × 70 × 20 mm / 200g		85 × 85 × 20mm / 210g	
Wire cross-section	SC-05SM/SM-Z: 1.5 mm ² ; SC-10SM/SM-Z: 2.5 mm ² ; SC-15SM/SM-Z: 4 mm ² SC-20SM/SM-Z: 4 mm ²			
Typical power consumption	Lower than 13mA / 15mA			
Working temperature	-40°C ~ 60°C			
Case protection	IP68			
Max altitude	4000 m			

Specifications are subject to change without notice.

OPTI-Solar Asia:
Tel: +886-2-2246-7272
Fax: +886-2-2246-7312
info@opti-solar.com

OPTI-Solar USA:
Tel: +1-909-869-5700
Fax: +1-909-869-5730
info@opti-solar.com

OPTI-Solar Middle East:
Tel: +9714-8819-838
Fax: +9714-8819-938
info@opti-solar.com

OPTI-Solar SENA:
Tel: +39 389 8428470
Fax: +39 011 19785932
info@opti-solar.com

OPTI-Solar Japan:
Tel: +81-3-3629-5782
Fax: +81-3-5682-0652
info@opti-solar.com