

SPM045P

FEATURE:

- IEC61215, TUV certification
- UL 1703 certification
- Using high efficiency 6" Multicrystalline cells.
- Using low iron tempered glass and an EVA pottant with TPT back sheet to encapsulated cells.
- Anodized aluminum frame protected structural strength.
- 10 years limited warranty of 90% power output and 25 years limited warranty of 80% power output.



High-efficiency, High-Quality Multicrystalline Photovoltaic Module

ASUN Energy manufactures clean, elegant and durable modules with advanced industry-leading performance for different electrical power requirements. It is designed and built to deliver highest efficiency and reliable power for on-grid residential and commercial systems worldwide.



ASUN 45Watt panels could applied in Electrification of villages in remote areas, Power source for summer vacation homes, Emergency communication systems, Microwave/radio repeater stations, Water quality and environmental data monitoring systems, Railroad signals, Pumping systems for irrigation, rural water supplies, Recreational Vehicles, etc.



ELECTRICAL CHARACTERISTICS			
	SPM045P	SPM040P	
Power at STC(Pm)	45W	40W	
Maximum power voltage(Vpm)	18.3V	17.3V	
Maximum power current(Ipm)	2.52A	2.35A	
Open circuit voltage(Voc)	22.2V	21.8V	
Short circuit current(Isc)	2.69A	2.57A	
Tolerance	±5%	±5%	
Module efficiency	13.10%	11.6%	
Maximum system voltage	1000V DC		
Standard test conditions	Temperature 25°C, Irradiance 1000W/m ² , AM=1.5		
Temperature coefficient	Isc:0.05%/K	Voc:-0.36%/K	Pmax:-0.46%/K

Specifications	
Cell	Multicrystalline silicon solar cell, (156mmx52mm)
No. of cell and connection	36 (6x6)
Dimension	987mm (38.9in)x384mm (15.1in)x35mm (1.38in)
Weight	5.5KG

AMBIENT CONDITIONS	
Operating Temperature	-40°C to +85°C
Storage Humidity	<90%

Output	
Type of output terminal	Junction box
Cable	Length 900mm

