

## SPECIFICATION OF 100W MONO SOLAR MODULE

### Mono-Crystalline

Module type	Pm(W)	Number of cell	Cell Dimension (mm)	Max System Voltage(V)	Vm(V)	Im(A)	Voc(V)	Isc(A)
TYSM100	100W	6*18	125	1000	18	5.56	22.36	6.57

### Parameter

Maximum system voltage (V)	1000
Temperature coefficients of Isc (%)	+0.1%/°C
Temperature coefficients of Voc (%)	-0.38%/°C
Temperature coefficients of Pm (%)	-0.47%/°C
Temperature coefficients of Im (%)	+0.1%/°C
Temperature coefficients of Vm (%)	-0.38%/°C
Temperature Range	-40°C ---85°C
Tolerance Wattage (e.g. +/-5%)	± 5%
Surface Maximum Load Capacity	60m/s (200kg/sq.m)
Junction Box Type	PPO, black
Connectors and Cables Type	4mm2
Length of Cables (mm)	900
Cell Efficiency (%)	>17%
Output tolerance (%)	± 5%
Frame (Material, Corners, etc.)	Anodized Aluminum Alloy
Standard Test Conditions	AM1.5 100MW/cm <sup>2</sup> 25°C
Warranty	5 years for the whole product, 90% power for 10years, 80% power for 25 years.



### Physical Characters

Output	Module Net Weight	Module Size (MM)	Packing Dimension (MM)	20' Container	40' Container
100W	10.5 (kg)	963*805*35	998*835*90	540 pcs	1100pcs



深圳市拓阳新能源科技有限公司

SHENZHEN TUOYANG NEW ENERGY CO.,LTD

Tel: +86-755-2305 5561 Mobile : +86-13717084860

www.sztuoyang.com

Email:szsytyn@163.com