



SPECIFICATION OF 20W POLY SOLAR MODULE

Poly-Crystalline

Module type	Pm(W)	Number of cell	Cell Dimension (mm)	Max System Voltage(V)	Vm(V)	Im(A)	Voc(V)	Isc(A)
TYSM20	20W	36	156	1000	18	1.15	22.100	1.28

Parameter

Maximum system voltage (V)	1000
Temperature coefficients of Isc (%)	+0.1%/°C
Temperature coefficients of Voc (%)	-0.38%/°C
Temperature coefficients of Pm (%)	-0.47%/°C
Temperature coefficients of Im (%)	+0.1%/°C
Temperature coefficients of Vm (%)	-0.38%/°C
Temperature Range	-40°C ---85°C
Tolerance Wattage (e.g. +/-5%)	± 5%
Surface Maximum Load Capacity	60m/s (200kg/sq.m)
Junction Box Type	PPO, black
Connectors and Cables Type	4mm ²
Length of Cables (mm)	300
Cell Efficiency (%)	>16.0%
Output tolerance (%)	± 5%
Frame (Material, Corners, etc.)	Anodized Aluminum Alloy
Standard Test Conditions	AM1.5 100MW/cm ² 25°C
Guarantee of power	5 years for whole products,90% power for 10years, 80% power for 25years.
FF (%)	≥73.3%

Physical Characters

Output	Module Net Weight	Module Size (MM)	Packing	20' Container	40' Container
20W	2.5(kg)	550*350*23	2pcs/carton	1792 pcs	3862 pcs

深圳市拓阳新能源科技有限公司

SHENZHEN TUOYANG NEW ENERGY CO., LTD

Tel: +86-755-2305 5561 Mobile : +86-13717084860

www.sztuoyang.com

Email:szsyty@163.com

