

TECHNICAL DATA SHEET

PS175M、 PS180M



Technical Data

Type	PS175M、 PS180M
Type of Solar Cell	Mono-crystalline, 125mm×125mm
Number of Cells	72 pcs
Size of module	1580×808×45mm (125×125mm cell)
Module, Weight	15.5 kg
Connector / Cross-Section	Cixi Renhe
Cables, Length (+/-)	900 mm
Front Cover Glass	Safety Glass
Front Cover Glass, Thickness	3.2 mm
Frame	Anodized Aluminium

Electrical Data

Maximum Power	$P_{MPP\ STC}$	175 W	180 W
Power Tolerance	Δ_{STC}	0~+3%	0~+3%
Maximum Power Voltage	$U_{MPP\ STC}$	35.2 V	36.0 V
Maximum Power Current	$I_{MPP\ STC}$	4.95 A	5.00 A
Open Circuit Voltage	$U_{OC\ STC}$	44.2 V	44.8 V
Short Circuit Current	$I_{SC\ STC}$	5.2 A	5.29 A
Cell Efficiency	η_{STC}	16.36 %	16.82 %
Maximum System Voltage	U_{DC}	1000V	1000V

STC: Irradiance 1000 W/m²; Spectrum AM 1,5; Cell Temperature 25°C, Wind 0 m/s

Temperature Coefficients

Power Coefficient	$\alpha_k (P_{MPP})$	- 0.45 %/K
Voltage Coefficient	$\beta_k (U_{OC})$	- 0.35 %/K
Current Coefficient	$\phi_k (I_{SC})$	0.065 ± 0.015 %/K

Power Warranty


10 years performance warranty to 90 %

25 years performance warranty to 80 %

5 years warranty against production and material defects

Certifications

IEC 61215, IEC 61730 ,TUV, CE, ISO9001:2000



Power Blessed Co., Ltd Add: No. 7237, Hunan Rd. Pudong Shanghai 201318, China

Tel:+86 21 58170702 Fax:+86 21 51062610 Email:info@powerblessed.com

