

YI6B

54/195-235P



YI6B-195-235P series module consists of 54 pieces of 156mm*156mm mono-crystalline silicon solar cells, which are in high efficiency. YI6B are widely used in on-grid system, including commercial, household and industrial large-scale solar power generation system. Yi-solar has the world-class quality certification and holds continued technological innovation. The company continues to meet the customer's demand for high quality products.

First-class Quality Assurance

- 10 years limited product materials and process warranty
- 25 years linear power output warranty



Product Feature



The design of black tape and borderless can meet the architectural aesthetic. Especially suitable for residential and rooftop commercial projects.



Gently module weight: the whole weight of module 18.5 kg is lighter than the conventional framed module 19.5kg.



The design of thinner and lighter modules is easier for the installation.



Ability to work under pressure, the modules can withstand the wind load of 2400Pa and snow load of 5400Pa.



Higher output power, module efficiency can be achieved to 16.31%.



Anti-reflection glass not only increases the absorption of light, but also has a self-cleaning function in the water environment. Reducing the power loss caused by dust effectively.



Excellent low-light power generation performance. (morning, evening and rainy days)




Products And System Certification

- IEC 61735, IEC 61730, CE
- ISO9001:2008:ISO Quality Management System
- CGC Golden Sun Certification



www.yi-solar.com
Liao Ning Yi-solar Energy
Technology Co. Ltd








Mechanical Parameters

Cell (mm)	Mono156x156
Weight (kg)	18.5
Dimension(L×W×H) (mm)	1482x990x50
Cable Sectional Area	4
No.of Cells	54(6x9)
No.of Diodes	6
Connector	MC4 Compatible joint
Packaging Information	26/26+2 Per Pallet

Working Parameters

Maximum System Voltage	DC 1000V(TÜV)
Operating Temperature	-40 C ~ +85 C
Maximum Fuse Rated Current	15A
Maximum Static Load Front(Wind Load,Snow Load)	5400Pa (112 lb/ft ²) 2400Pa (50 lb/ft ²)
Normal Operating Cell Temperature	45±2 C
Application Class	Class A

I-V Curve



Electrical Parameters (Standard Test Condition)

Module Type	YI6B-195P	YI6B-205P	YI6B-210P	YI6B-215P	YI6B-220P	YI6B-230P
Maximum Power (W)	195	205	210	215	220	230
Open Circuit Voltage (Voc/V)	32.62	32.81	32.92	33.01	33.50	33.55
Maximum Operating Voltage (Vmp/V)	26.58	27.05	27.44	27.67	28.00	28.23
Short Circuit Current (Isc/A)	8.09	8.27	8.34	8.41	8.49	8.53
Maximum Operating Current (Imp/A)	7.35	7.59	7.65	7.77	7.86	8.10
Module Efficiency [%]	13.30	13.98	14.31	14.65	14.99	15.68
Power Tolerance (W)	±3%					
Short Circuit Current (Isc)Temp.Coefficient (αIsc)	+0.049%/°C					
Open Circuit Voltage (Voc)Temp.Coefficient (βVoc)	-0.340%/°C					
Maximum Power (Pmp)Temp.Coefficient (γPmp)	-0.430%/°C					
Standard Test Condition	Irradiation Intensity 1000W/m ² , Module Temperature 25°C, Spectrum AM 1.5					