



XINSHUN PV

### Electrical Data

Module Type	XSSP240P30	XSSP245P30	XSSP250P30	XSSP255P30
Nominal peak power (Wp)	240	245	250	255
Nominal voltage (Vmp)	31.08	31.32	31.74	31.98
Nominal current (Imp)	7.75	7.82	7.90	7.98
Open circuit voltage (Voc)	37.2	37.38	37.74	37.92
Short circuit current (Isc)	8.49	8.55	8.62	8.68
Module efficiency	>14.8%	>15.1%	>15.4%	>15.7%
Operating Temperature	-45—+85°C			
Maximum System Voltage	1000VDC			
STC: AM1.5,1000W/m <sup>2</sup> ,25°C				




### Temperature Coefficients

NOCT:47 ±2°C
Voltage temperature coefficient (Voc): -0.36%/ °C
Current temperature coefficient (Isc): +0.03%/ °C
Power temperature coefficient (Pmmp): -0.40%/ °C
Minimum power tolerance: ±3%
NOCT: Nominal Operating Cell Temperature

### Mechanical Data


Solar cell: 60 Polycrystalline 156x156mm			
Output Cables: 900mm length/compliable with MC IV connectors			
Dimension: 1640×990×45mm			
Junction Box:IP65 Rated		Front Glass:3.2mm tempered	
Frame:Anodized aluminium		Weight: 18.6Kg	
20 Gp	Packing Size:1690*1030*1130mm		40 HP
	Volume:1.97m <sup>3</sup>		
	Weight Per set:445Kg		
	Pallets:21*2=42Pcs		
Quantity:3*2*42=252Pcs		Packing Size:1690*1150*1130mm	
		Volume:2.20m <sup>3</sup>	
		Weight Per set:485Kg	
		Pallets:23*2=46Pcs	
		Quantity:7*2*46=644Pcs	

### Typical Electrical Characteristics





XINSHUN PV




### Warranty

**10 years workmanship**

**90% power output after 10 years**

**80% power output after 25 years**



Tel: (+86 579) 89092727 Fax: (+86 579) 8777 6703

E-mail: [xinshun@xinshungroup.com](mailto:xinshun@xinshungroup.com) Website: <http://www.xinshunpv.com>

Add: Baiyang Avenue, Baiyang Economic Development Zone Wuyi County Zhejiang

P.C.: 321200