





FEATURES:

- Single crystalline silicon photovoltaic module.
- High power module using 6” mono crystalline solar cell.
- Bypass diode is attached minimize power reduction caused by shade.
- 60 solar cells and connection in series.
- Using optical low iron tempered glass, EVA resin, module with aluminum frame for outdoor use.
- The module will maintain 90% of minimum specification performance along the first 12 years, and will maintain 80% of minimum specification performance along sequent 13 years.

LM245BA6A00 ~ /LM270BA6A00

Maximum power (Pmax)	245W	250W	255W	260W	265W	270W
Maximum power voltage (Vpm)	29.85 V	29.94 V	30.04 V	30.13 V	30.22 V	30.31 V
Maximum power current (Ipm)	8.21 A	8.35 A	8.49 A	8.63 A	8.77 A	8.91 A
Open circuit voltage (Voc)	37.62 V	37.80 V	37.92 V	38.10 V	38.22 V	38.40 V
Short circuit current (Isc)	8.84 A	8.98 A	9.12 A	9.26 A	9.40 A	9.54 A
Module efficiency (ηm)	15.2%	15.5%	15.8%	16.2%	16.5%	16.8%
No. & type solar cells	60 in series/ 6”(156x156 mm) single					
Maximum system voltage	TUV:DC 1000 V/UL:DC 600 V					
Series fuse rating	15 A					
Performance tolerance	±3%					
Operating temperature	-40 to +90 °C					
Storage temperature	-40 to +90 °C					
Dimensions	1626x990x38.1 mm±2 mm/64”x39”x1.5”±0.08”					
Weight	20.0 kg/44.09 lbs					
Output Terminal(Tyco J-Box)	1394462-4(-)/6-1394461-2(+)					




Temperature coefficient of Isc: 0.04%/°C

Power temperature coefficient: -0.43%/°C

Temperature coefficient of Voc: -0.33%/°C

NOCT: 46±1°C

OUTLINE DIMENSIONS



Field wiring: Cu wiring only, min. 12 AWG(4mm²), insulated for 90°C min.