




## Polycrystalline Specification



Model	LIGP156-180W	LIGP156-190W	LIGP156-200W	LIGP156-210W	LIGP156-220W	LIGP156-230W
Maximum power at (Pm)	180W	190W	200W	210	220W	230W
Voltage at Pmax (Vmp)	23.5V	23.5V	27.21V	27.54	29V	29.4V
Current at Pmax (Imp)	7.66A	8.08A	7.36A	7.63	7.58A	7.82A
Open-circuit voltage (Voc)	29.04V	29.2V	32.72V	32.83	36.3V	36.5V
Short-circuit current (Isc)	8.1A	8.41A	7.86A	8.3	8.1A	8.3A
Maximum system voltage (VDC)	1000V	1000W	1000V	1000	1000V	1000V
No. cells and connections	48(8*6)	48(8*6)	54(9*6)	54(9*6)	60(10*6)	60(10*6)
Type of output terminal	Junction box	Junction box	Junction box	Junction box	Junction box	Junction box
Cable	4mm2	4mm2	4mm2	4mm2	4mm2	4mm2
Cable lengths	1000mm	1000mm	1000mm	1000mm	1000mm	1000mm
Dimension of module(mm)	1337*999*47	1337*999*47	1496*999*47	1496*999*47	1655*999*47	1655*999*47
Weight(Kg)	15.6	15.6	18.8	18.8	18.8	18.8
Power Output Warranty	25 years	25 years	25 years	25 years	25 years	25 years