



SHENZHEN ZHIHE SLOAR ELECTORIC CO.,Ltd

Building, Room 1012 Led Solar Silicon Valley Queshan Dalang Longhua ShenZhen

Web:www.zhihesolar.com

Model(ZH25CE-18P)Specifications	
ITEM NO.:	ZH25CE-18P
Maximum Power(W)	25
Optimum Power Voltage(Vmp)	17.49
Optimum Operatige Current(Imp)	1.42
Open Circuit Voltage(Voc)	21.67
Short Circuit Current(Isc)	1.52
Solar Cell:	156*32 Poly
Number of Cell(pcs)	3*12
Brand Name of Solar Cells	Jetion Cell
Size of Module(mm)	515*470*28
Front Glass Thikness(mm)	3.2
Temperature Coefficients of Isc(%)°C	+0.04
Temperature Coefficients of Voc(%)°C	-0.38
Temperature Coefficients of Pm(%)°C	-0.47
Temperature Coefficients of Im(%)°C	+0.04
Temperature Coefficients of Vm(%)°C	-0.38
Temperature Range	-40°C to +85°C
Tolerance Wattage(e.g.+/-5%)	±5%
Surface Maximum Load Capacity	2400Pa
Allowable Hail Load	23m/s ,7.53g
Weight Per Piece(KG)	3.90
Cell Efficiency (%)	13.91%
Module Efficiency (%)	10.32%
Frame(Material Corners,etc.)	28#
Backing (Brand Type)	TPT
Warranty	90% of 10 years,80% of 25 years.
Standard Test Conditions	AM1.5 1000W/m ² 25 +/-2°C
FF (%)	70-76%

Model(ZH25CE-18P)

Specification

ZhiHe Solar Module

Using high quality materials to provide
high quality solar modules

- 1.Solar cells:Jetion cells
- 2.Glass:Fiat 's from Shanghai
- 3.EVA:First Hot-Melt Adhesive from Hangzhou China
- 4.TPT:JOLYWOOD from Suzhou,China
- 5.Junction box and connectors:GZX from Cixi,China or Rehe from Cixi,China
- 6.Silica gel:Dow Corning

