

Play it safe



**Next
Generation**

Premium Modules
MADE IN GERMANY

Premium XM mono black
Premium incell XM mono black
200 W • 205 W • 210 W

- Plus-sorted
- Elegant black module for aesthetically demanding projects
- Guaranteed high yields for decades
- Premium XM: Improved innoframe stability
Premium incell XM: For roof-integrated systems – with patented SOLRIF® frame



Premium XM mono black / Premium incell XM mono black

Electrical data under STC (Standard Test Conditions: 1000 W/m², 25 °C, AM 1.5)

Rated power	P_{max}	200 W	205 W	210 W
Sorting limits of performance		0/+5 W	0/+5 W	0/+5 W
Voltage	U_{MPP}	24.25 V	24.56 V	24.86 V
Open circuit voltage	U_{OC}	30.09 V	30.40 V	30.70 V
Current	I_{MPP}	8.25 A	8.35 A	8.45 A
Short-circuit current	I_{SC}	8.73 A	8.83 A	8.93 A
Efficiency	Premium XM mono black	14.8 %	15.2 %	15.6 %
	Premium incell XM mono black	14.7 %	15.0 %	15.4 %

Electrical data at 800 W/m², NOCT (45°C +/- 2K), AM 1.5

Power in MPP	P_{max}	152 W	156 W	160 W
Voltage	U_{MPP}	22.86 V	23.15 V	23.44 V
Open circuit voltage	U_{OC}	27.84 V	28.13 V	28.41 V
Current	I_{MPP}	6.65 A	6.73 A	6.81 A
Short-circuit current	I_{SC}	7.04 A	7.12 A	7.20 A

The efficiency decreases by approximately 3% compared to the efficiency under STC at an irradiation of 200 W/m² and 25 °C.

Temperature data

Power temperature coefficient	$T_K(P_{MPP})$	-0.47 %/K
Voltage temperature coefficient	$T_K(U_{OC})$	-0.33 %/K
Current temperature coefficient	$T_K(I_{SC})$	0.03 %/K

Further information

Number of cells	48
Max. system voltage	1000 V
Reverse current loading capability	17 A
Front cover	Special hardened low-iron glass with anti-reflex coating; Glare reduced to a minimum
Module connection	Junction box 3 bypass diodes IP 67 no potting, 2 x approx. 1 m solar cable Ø 4 mm ² , plug connector PV4 IP 68
Snow load*	Premium XM mono black Premium incell XM mono black innoframe framed: 5400 Pa $\hat{=}$ 550 kg/m ² With SOLRIF®: 5400 Pa $\hat{=}$ 550 kg/m ²

12-year product warranty, 25-year linear performance warranty according to our additional warranty conditions for solar power modules of the "Premium" product series, which we will gladly send you

Subject to technical modifications with corresponding follow-up certifications. Errors excepted.


*Load tested according to EN IEC 61215 (ed. 2) In compliance with the installation and operating manual.

**SOLRIF® in-roof mounting system, TÜVdotCom certified. The manufacturer of this system, Ernst Schweizer AG, Hedingen, Switzerland, gives Solar-Fabrik a guarantee of 10 years on the delivered material and the parts of the system, in accordance with the guarantee terms of Schweizer, which we will gladly provide if requested. Guarantee claims will be processed for you by Solar-Fabrik. This guarantee warranted by Ernst Schweizer AG does not include the solar modules and does not affect the contractual warranty of Solar-Fabrik. by Ernst Schweizer AG does not include the solar modules and does not affect the contractual warranty of Solar-Fabrik.



Certifications

EN IEC 61215 (ed. 2)¹
EN IEC 61730-1, -2¹
EN 13501-1, class E
Protection class II
Directive 2006/95/EG (CE)
MCS
TÜVdotCOM (Solrif® frame)**
Hail protection class 3

¹Subject to follow-up certifications.




Premium XM
mono black
Weight:
approx. ca. 15 kg



Frameless modul
dimensions:
991 x 1344 mm

Premium incell XM
mono black
Weight:
approx. 17 kg



Note: Ensure correct polarity!

Your specialist dealer:

Solar-Fabrik AG
Munzinger Str. 10
79111 Freiburg
Germany
Phone +49 (0)761 4000-0
Fax +49 (0)761 4000-199
info@solar-fabrik.de
www.solar-fabrik.de