


## SHENZHEN JINGUANGNENG SOLAR-ENERGY CO.,LTD

ADD: Build 16,Lantian Science And Technology Park, Ditang Rd, Shajing Town,Shenzhen City, China.

TEL: +86-755-81467690. FAX: +86-755-81467556

E-MAIL: [sales01@jnsolar.com](mailto:sales01@jnsolar.com) WEBSITE: [www.cnsolarpower.com](http://www.cnsolarpower.com)

Product Name	Solar module	Model	CY-TD10
	Peak Power (Pm) (W)		10W
	Maximum Power Voltage Vm (V)		18V
	Maximum Power Current Im (A)		0.56A
	Open Circuit Voltage Voc (V)		21.24V
	Short Circuit Current Isc (A)		0.61A
	Maximum System Voltage (V)		1000V
	Cells Type (Mono/Poly)		Mono
	No. Of Cells and Connection (PCS)		36PCS (2*18)
	Cells Dimension (mm)		125x125
	Pm Temperature Coefficient (%/°C)		-0.45%/°C
	Voc Temperature Coefficient (%/°C)		-0.35%/°C
	Tolerance (%)	±3%	IscTemperature Coefficient (%/°C)
Dimension (mm)	330*290*25mm	Standard Test Condition(STC)	Aml.5 25°C 1000W/m²
Net Weight (Kg)	1.5Kg	WorkingTemperature range(°C)	-40°C~90°C
Gross weight	20Kg	Packing quantity (pcs)	10pcs/carton
Product component	Tempered Glasses + EVA + Solar Cells + EVA + TPT + Aluminum Frame + International Standard Junction Box		
Glasses	low carbon Tempered Glasses	Frame Type	25 x 20mm Aluminum Frame
Junction box	International Standard Junction Box		
Certificate	TUV : CE : ROHS : IEC61215 : CGC		
Warranty	5 years for full product power, 10 years for 90% product power, 25 years for 80% product power.		

