



Moude (SL220CE-30P) Specifications

ITEM NO. :	SL220CE-30P		
Maximum Power (W)	220	210	200
Optimum Operating Voltage (Vmp)	29.28	29.28	29.28
Optimum Operating Current (Imp)	7.51	7.17	6.83
Open Circuit Voltage (Voc)	36.00	36.00	36.00
Short Circuit Current (Isc)	8.03	7.67	7.31
	156*156 Poly		
Number of Cell (pcs)	6*10		
Brand Name of Solar Cells	OEM		
Size of Module (mm)	1640*980*40		
Cable & Connector Type	Pass the TUV Certificate		
	Aluminium-alloy		
Backing (Brand Type)	TPT		
	15%		
	18.96		
FF (%)	70-76%		
	Pass the TUV Certificate		
Tolerance Wattage (e.g. +/-5%)	±5%		
	3.20		
Temperature Coefficients of Isc (%) °C	+0.04		
Temperature Coefficients of Voc (%) °C	-0.38		
Temperature Coefficients of Pm (%) °C	-0.47		
Temperature Coefficients of Im (%) °C	+0.04		
Temperature Coefficients of Vm (%) °C	-0.38		
Temperature Range	-40°C to +85°C		
Surface Maximum Load Capacity	2400 Pa		
Allowable Hail Load	23m/s, 7.53g		
Bypass Diode Rating (A)	12		
	90% of 10 years, 80% of 25 years.		
Standard Test Conditions	AM1.5 1000W/ m2 25+/-2 °C		
Packing			
1*20'	14 Pallets / 316 pcs		
1*40'HQ	28 Pallets / 756 pcs		

