



Moude (SL135CE-27M) Specifications

	SL135CE-27M		
Maximum Power (W)	135	125	115
Optimum Operating Voltage (Vmp)	26.36	26.36	26.36
Optimum Operating Current (Imp)	5.12	4.74	4.36
Open Circuit Voltage (Voc)	32.4	32.4	32.4
Short Circuit Current (Isc)	5.48	5.07	4.66
	125*125 Mono		
	6*9		
	OEM		
	1200*808*40		
	Pass the TUV Certificate		
Frame (Material Corners, etc.)	Aluminium-alloy		
	TPT		
	16.0%		
	12.7		
	70-76%		
	Pass the TUV Certificate		
	±5%		
	3.20		
Temperature Coefficients of Isc (%) °C	+0.04		
Temperature Coefficients of Voc (%) °C	-0.38		
Temperature Coefficients of Pm (%) °C	-0.47		
Temperature Coefficients of Im (%) °C	+0.04		
Temperature Coefficients of Vm (%) °C	-0.38		
Temperature Range	-40°C to +85°C		
Surface Maximum Load Capacity	2400 Pa		
Allowable Hail Load	23m/s, 7.53g		
Bypass Diode Rating (A)	12		
Warranty	90% of 10 years, 80% of 25 years.		
Standard Test Conditions	AM1.5 1000W/ m ² 25+/-2°C		
Packing			
1*20'	18 Pallets / 474 pcs		
1*40'HQ	36 Pallets / 972 pcs		

