



Solartech
Energy Corp.

285W-310W

Maximize solar return with
Solartech
High Performance Modules



ASC-6P-72-3BB Series

Multi-Crystalline Photovoltaic Modules

Maximize peak output with pre-sorted high quality 6" multi-crystalline cells

Ensure 5400pa snow loads and 2400pa wind loads with high transparent tempered glass and robust anodized aluminum frame

Commit protection in the severest weather conditions with certified EVA, Back sheet foil, and Junction box


10-year limited product warranty, 25-year limited power output warranty (90% for 10 years, 80% for 25 years)



ASC-6P-72-3BB Series 285W-310W

Multi-Crystalline Photovoltaic Modules


Mechanical Data



Dimension: 1960mm x 992mm x 40mm
 Cells: 72 polycrystalline 156x156mm cells
 Connection: Junction box IP65 with 3 bypass diodes
 Cable: 4mm²x1.0m with Tyco or MC4 compatible connectors
 Frame: Anodized aluminum
 Weight: 23 kg / 50.71 lbs

IV Curve

IV and Pmax Curves with different radiation levels at 25°C



Temperature Coefficient

Temp. Coeff. of Isc = 0.05%/K
 Temp. Coeff. of Voc = -0.32%/K
 Temp. Coeff. of Pmax = -0.47%/K

Maximum Operation

Operational Temperature: -40°C to +85°C
 (-40°F to +185°F)
 Maximum System voltage: 1000V DC
 Maximum Reverse Current: 15A
 Maximum Load: Snow load 5400pa or 550kg/m²
 Wind load 2400pa

Loading Capacity

20 ft container: 230 pcs (23pcs/pallet)
 40 ft container: 506 pcs (23pcs/pallet)
 40 ft HQ container: 594 pcs (27pcs/pallet)

Electrical Characteristics @ STC*

Module Number	ASC-6P-72-285-3BB	ASC-6P-72-290-3BB	ASC-6P-72-295-3BB	ASC-6P-72-300-3BB	ASC-6P-72-305-3BB	ASC-6P-72-310-3BB
Nominal Power Pmax[Wp]	285	290	295	300	305	310
Power Tolerance **	+3%	+3%	+3%	+3%	+3%	+3%
Nominal Voltage Vmax[V]	36.02	36.16	36.38	36.45	36.53	37.30
Nominal Current Imax[A]	7.91	8.02	8.08	8.23	8.35	8.31
Open Circuit Voc[V]	44.32	44.46	44.68	44.75	44.83	45.18
Short Circuit ISC[A]	8.41	8.52	8.58	8.62	8.68	8.70
Efficiency Eff [%]	14.66	14.92	15.17	15.43	15.69	15.94

*STC: Standard Test Conditions, measurement at radiation strength 1,000 W/m², spectral distribution AM 1.5, temperature 25°C, in accordance with EN 60904-3

**Power tolerance can be adjusted on requests

NOCT: Nominal Operating Cell Temperature, 45.8 +/- 2°C, measurement at radiation strength 800 W/m², AM 1.5, Air temperature 20°C, wind speed 1m/s

Specifications are subject to change without notice

Warranty

10 year limited product workmanship warranty

25 year limited power output warranty: 90% minimum rated power for 10 years. 80% minimum rated power for 25 years

Solartech Energy Corp.

Taipei Office
 8F., No.760, Sec. 4, Bade Rd., Songshan Dist., Taipei City 105, Taiwan
 Tel: +886-2-21712388 Fax: +886-2-21712387 E-mail: sales@solartech-energy.com

Hsinchu HQ & Fab
 No. 16, Guangfu N. Rd., Hsinchu Industrial Park, Hukou, Hsinchu 303, Taiwan
 Tel: +886-3-5276888 Fax: +886-3-5246866