

Mono-Crystalline



SALIENT FEATURES

- Range start from 3W – 250W.
- High quality, Low price.
- 25 year warranty.
- Weather Proof, high wind pressure and snow load.
- High conversion efficiency.

SPECIFICATION	3W	5W	10 W	20 W	40 W	50 W	75 W	100 W	150 W	150 W	200 W	250W	
Panel Type: NL-	3	5	10	20	40	50	75	100	150	150	200	250	
Wattage (W):	3	5	10	20	40	50	75	100	150	150	200	25	
Tolerance:	+/- 5%										+/- 3%		
Width (mm):	195	195	360	360	675	675	666	676	1006	1006	982	982	
Height (mm):	195	300	295	495	445	565	796	1151	1006	1006	1639	1639	
Thickness (mm):	22	22	22	22	30	30	35	35	35	35	35	35	
Weight (kg):	0.5	0.85	1.6	2.5	4	4.78	6.8	8.6	13	13	20.3	20.3	
Voc (V):	10	10	21.4						44.38		35.9	37.25	
Isc(A):	0.7	0.85	0.94	1.4	2.65	3.25	4.6	6.5	8.7	4.7	7.9	8.95	
PMax(W):	3W	5	10	20	40	50	75	100	150	150	200	250	
Vpm(V):	8.2	8.3	17.7						34.1		27.8	29.5	
Ipm (A):	0.4	0.6	0.6	1.15	2.3	2.85	4.25	5.7	8.5	4.4	7.2	8.5	
Cell in series:	18			36						72		60	
Module Volt (V) :	6		12								24		
Mounting Hole Dimension (mm):				6.9									
Mounting Hole (X-Axis) (mm):				639		630	640	970		946			
Mounting Hole (Y-Axis) (Distance between two Holes) (mm):				223	282.5	398	575.5	503		819.5			
Maximum System Voltage (V):	600						1000						