



**SOLAR POWER VIETNAM TECHNOLOGY JOINT STOCK COMPANY**  
Office: 86/58 Pho Quang St., Ward 2, Tan Binh Dist., HCM City  
Factory: 230-230A Vo Van Bich St., Village 4B, Binh My Ward, Cu Chi Dist., HCM City  
Email: solarvietnam.vn@gmail.com  
ĐT: (08) 2227 8338  
[www.solarvietnam.vn](http://www.solarvietnam.vn)  
**GREEN POWER GREEN LIFE**

## PROFORMA INVOICE of SPV 150Wp POLY SOLAR PANEL

Maximum Power Pmax Range	150 Wp -155Wp
Voltage at Maximum Power Point Vmp (V)	18.58
Current at Maximum Power Point Imp (A)	8.07
Open Circuit Voltage Voc (V)	22.67
Short Circuit Current Isc (A)	9.23
Dimension Panel (mm)	1480 x 680 x 40
Solar cell	Solar world cell - Polycrystalline : 156X156MM , 36 PCS
Cells Efficiency (%)	18.00% - 18.20%
Module Efficiency (%)	16.2% - 16.30%
Weight (Kg)	< 12 kg
Warranty	10 years > 90% power
Frame	Anodized Aluminium Alloy
Solar cell	Solar World - Monocrystalline cell (Germany)
Glass	Tempered-Thickness 3.2 mm, Nano Coating, 277g steel ball dropped from 1m height and wind 60m/s
J-Box	IP65 RATED
Diodes	6pcs x 6A
Output cables	4mm <sup>2</sup> , length 1000mm
Connectors	Amphenol male and female
Operating Module Temperature	-40°C to +85°C
Minimum Order	
Port	Cat Lai Port, Ho Chi Minh City, VN
Price per Panel	
Payment Term	40% TT in advance as deposit 60% T/T before COPY Bill
Packaging Details	2 pcs in Carton Box, 732pcs/20'GP
Delivery Detail	10 - 20 working days

**CERTIFICATION: TUV SUD**