




SPECIFICATION OF 70W,75W,80W POLY SOLAR MODULE

PRODUCT SPECIFICATION

Type Of Module	AE70P(36)	AE75P(36)	AE80P(36)
Maximum Power (W) 功率	70	75	80
Tolerance (%) 正负公差	± 3%	± 3%	± 3%
Open Circuit Voltage (V) 开路电压	21.96	21.96	21.96
Maximum Power Voltage (V) 工作电压	17.57	17.57	17.57
Maximum Power Current (A) 工作电流	3.98	4.27	4.55
Short Circuit Current (A) 短路电流	4.8	5.1	5.5
Module Efficiency (%) 组件转换率	13.8	14.8	15.8
Solar Cell Efficiency (%) 电池片转换率	16	17.1	18.3
Series Fuse Rating (A) 保险丝等级	10	10	10
Terminal Box 接线盒防水等级	IP65	IP65	IP65
Maximum system voltage (V) 系统耐压	DC1000	DC1000	DC1000
Operating Temperature(°C) 工作温度范围	-40°C ---85°C	-40°C ---85°C	-40°C ---85°C



PRODUCT FEATURE

- Bypass diode minimizes the power drop by shade.
- The conversion efficiency of solar cell is above 15.5%.
- White tempered glass ,EVA resin,weather proof film and anodized aluminum frame to provide efficient protection from the severest environmental conditions.
- Waterproof.Perfect for grid applications.
- Product guarantee 5 years.


Quality Assurance

- Electrical Insulation test
- Outdoor exposure test
- Hot-spot endurance test
- UV-exposure
- Thermal cycling test
- Humidity freeze test
- Damp heat Test
- Robustness of terminations test
- Wet leakage current test
- Mechanical load test
- Hail impact test
- Bypass diode thermal test



Electrical Characteristics

Current-Voltage & Power-Voltage characteristics various irradiance levels



Electric Performance Typical Performance Characteristics

Short Circuit Current Temperature Coefficient	mA/C	+2.5
Open Circuit Voltage Temperature Coefficient	V/C	-0.147
Maximum Power Temperature Coefficient	%/C	-0.4
Performance Warranty : 90%output , 12 years 80%output, 25 years		

Physical Specifications

Dimension: 758*670*30*25mm

Weight: 6.5KG/PCS

Packing : 2pcs in one carton

Loading Capacity:

1300pcs/ 20' Container

2700 pcs/ 40' Container

ATONE NEW ENERGY LIMITED



Add:Industrial Zone, changzhou city, Jiangsu province.China.

Website:www.atoneenergy.com, Email:atone@atoneenergy.com Contact:Tel:86 519 8309070 Fax:86 519 83090702

Mobile Phone/What's up:86 138 135 46477

Skype:.sammy2008.cool