

Module 组件	TDM260P-B-60		
Series 串联	3BB-PB-60		
Encapsulation 封装	Glass/EVA/Cell/EVA/TPT 玻璃/EVA/电池片/EVA/背板		
Size and Number of cells 电池片尺寸和数量	156mm*156mm 60/10*6pcs 156 毫米*156 毫米 60/10*6pcs		
Pmax 最大功率 (W)	260	255	250
Cell Efficiency 电池效率 (%)	18.20	17.80	17.50
Module Efficiency 组件效率 (%)	16.01	15.71	15.40
Tolerance 公差	+3%		
Voc 开路电压 (V)	37.80	37.60	37.40
Isc 短路电流 (A)	8.69	8.61	8.54
Vmp 最大功率电压 (V)	31.60	31.40	31.00
Imp 最大功率电流 (A)	8.23	8.13	8.07
Max. Syst. Open Voltage 最大系统开路电压 (V)	1000		
Diodes 二极管	3by-pass		
Dimension 尺寸 (mm)	1640×990×50 / 1640×990×40		
Weight 重量 (kg)	21/19		
MAX Over Current Protecng Rating 最大过电流保护率 (A)	15		
Operate Temp Scope 操作温度范围℃	-40~+85		
Relative humidity 相对湿度%	0~100%		
Frame Thickness 边框厚度	Quantity 数量/Container 集装箱		
50mm	264pcs/20GP	728pcs/40HQ	
Cell Technology 电池片技术	multi-Si		

Output

Cable	4.0mm ² (TUV)	Length	950mm	Connector	MC Type
-------	--------------------------	--------	-------	-----------	---------

