



Polysolar

PS -CT-Series Opaque panels

STC Product Specifications for CdTe thin-film glass/glass laminate opaque BIPV glazing units



Polysolar's black opaque thin-film PS-CT series is a high efficiency panel with side or back connectors

High energy yield 118 Watts/m²

Highly aesthetic black finish

Works down to ambient light levels

Less position sensitive

Bespoke sizing available

Single or double glazed panels available



APPROVED PRODUCT





Physical Specifications PS-CT-Series Opaque

Active Material of Cell		Cadmium Telluride (CdTe)
Encapsulation Material		Polyvinyl butyrate (PVB) thickness 0.76 mm
Front Cover		Float Glass, thickness: 3.2 mm
Back Cover		Tempered Glass, thickness: 3.2 mm
Wiring Material		Tin & silver coated copper ribbon thickness 0.1 mm
Junction Box	Bypass diode	10 A
	IP Class	IP 65
Cable length		700 mm (+) 700 mm (-) side mounted junction box or 650 mm (+) 650 mm (-) back mounted junction box
Connecting Cable Plug		Rated voltage 1000 Volts D.C. Temperature range: -40 to 85 °C Plug/Socket MC4 compatible Ø 4 mm Cable cross section: 2.5 mm ²
Transparency		Variable 0-40%
Frame		Frameless
Dimensions	Width	600 mm+2/-1 mm
	Length	1200 mm +2/-1 mm
	Thickness	6.8 mm+2/-1 mm
Weight		11.8 kg
The module is tested under 2400 Pa (50 lb/ft ²) mechanical load or approximately to a wind speed of 130 km/h (80 mph) with certified mounting solutions. Other mounting solutions for higher mechanical loads are also available and can be warranted by Polysolar		

Electrical Specifications PS-CT-Series Opaque

Polysolar Model	Class	Stabilized Performance STC			
		V _{mpp} (V)	I _{mpp} (A)	V _{oc} (V)	I _{sc} (A)
PS-CT-85 Opaque	85W	96.6	0.88	120.5	0.98
Max over current rating	2.0 A				
Temp Co-efficient	I _{sc} +0.06%/K V _{oc} -0.32%/K P _{mpp} -0.21%/K				
Max System Voltage	1000 Vdc				


The unit's electrical ratings are measured under Standard Test Conditions (STC) and have been delivered on the specific table of electrical characteristics as shown above. A photovoltaic module may produce more current and/or voltage than reported at STC. Sunny, cool weather and reflection from snow or water can increase current and power output. Therefore, the values of I_{sc} and V_{oc} marked on the units should be multiplied by a factor of 1.25 when determining component voltage ratings, conductor capacities, fuse sizes, and size of controls connected to PV output. [STC]: 1000 W/m², AM 1.5, 25 °C. The exactly measured electrical characteristics are shown on the label of the units.



Polysolar

Warranty

Warranty on Product (Workmanship & Materials)	Warranty on Performance (Power Grade Output)
10 years from date of shipment	90% of power grade output of the module for a 10 year period and then 80% of the power grade output of the module for a 25 year period from date of shipment
Certifications	IEC EN6164 & 61730-1 & 61730-2 MCS 017 (BSI) Kitemark CE Mark





Polysolar

www.polysolar.co.uk

Tel: (+44) 01223 911534

Email: info@Polysolar.co.uk



*World leaders in the design, development and project management of Building
Integrated Photovoltaic solutions*

Cambridge Office

Polysolar Limited
Hauser Forum
Charles Babbage Road
Cambridge CB3 0GT
UK

London Office

Polysolar Limited
One Canada Square
Canary Wharf
London E14 5AB
UK