



**EEEEASILY
MORE.**

Excellent. Efficient. Expert.



The Value-Added Modules of the IBC SOLAR Line.

IBC SoloSol 155 CS4

First-class solar modules made of polycrystalline silicon



25 year power and 10 year product warranty¹



Positive power tolerance (-0/+5 Wp)



Increased mechanical stability (5400 Pa)²



German warrantor



100% tested quality



Maximum transparent ARC glass

IBC SOLAR – your partner for energy solutions

IBC SOLAR AG has had a successful presence in the photovoltaic market for **more than 35 years** and is one of the leading international energy companies providing high-performance system solutions in every size and for every application with intelligent photovoltaic systems. The **economic strength and financial independence** is confirmed by globally recognised rating agencies.

Smart Systems for Solar Power thanks to perfectly matched components. **More than 1,000 highly qualified partners** around the world, as well as **more than 3,000 megawatts of installed power**, which supply **around 2 million people with solar power**, underline the high level of expertise of IBC SOLAR.

IBC SOLAR – leading PV system integrator from Germany since 1982!



Engineered in
GERMANY

The ideal solution for:



TECHNICAL DATA

IBC SoloSol	155 CS4
Article number	2203800021 2203800025

Electrical data (STC):	
STC Power Pmax (Wp)	155
STC Nominal Voltage Umpp (V)	18.33
STC Nominal Current Impp (A)	8.19
STC Open Circuit Voltage Uoc (V)	24.08
STC Short Circuit Current Isc (A)	8.6
Module Efficiency (%)	15.7
Power Tolerance (Wp)	-0/+5

Electrical data (NOCT):	
800 W/m ² NOCT AM 1.5 Power Pmax (Wp)	115.84
800 W/m ² NOCT AM 1.5 Nominal Voltage Umpp (V)	17.04
800 W/m ² NOCT AM 1.5 Open Circuit Voltage Uoc (V)	22.43
800 W/m ² NOCT AM 1.5 Short Circuit Current Isc (A)	7.75
Relative Efficiency Reduction at 200 W/m ² (%)	4.3


Temperature coefficient:	
NOCT (°C)	46
Tempcoeff Isc (%/°C)	+0.044
Tempcoeff Voc (mV/°C)	-76.33
Tempcoeff Pmpp (%/°C)	-0.423

Operating conditions:	
Max. System Voltage (V)	1000
Application Class	A
Reverse Current Ir (A)	15
Current value string fuse (A)	15
Fuse protection from parallel strings	3

Mechanical properties:	
Dimensions (L × W × H in mm)	1476 × 666 × 35
Weight (kg)	12.5
Load capacity (Pa) ²	5400
Front sheet (mm)	3.2 (low-iron photovoltaic glass)
Frame	anodized aluminium, sturdy hollow-chamber frame
Cells	4 × 9 polycrystalline silicon cells
Connection type	MC4 (IP65)

Warranties and certification:	
Product warranty	10 years ¹
Power warranty	12 years 90%. 25 years 80% ¹
Certification	IEC 61215. IEC 61730-1/-2. ISO 9001. ISO 14001. OHSAS 18001

Packaging information:	
Number of modules per pallet	27
Number of pallets per 40 container	45
Dimensions incl. pallet (L × W × H in mm)	1550 × 1130 × 810
Gross weight incl. pallet (kg)	353
Stackability per pallet	2-fold



Presented by:

¹⁾ The warranty presupposes installation in accordance with the valid installation instructions.

Standard test conditions: 1000 W/m² irradiation with a spectral distribution of AM 1.5 and a cell temperature of 25 °C. 800 W/m², NOCT. Information according to EN 60904-3 (STC).

All values according to DIN EN 50380. The precise conditions and content can be taken from the respectively valid version of the product and power warranty, which you obtain from your IBC Premium Partner. Subject to errors and modifications.

²⁾ Tested according to IEC 61215 for snow loads up to 5400Pa (5.4 kN/m²).