
Mono-Crystalline 10W Solar Panel

Technical parameter

Maximum Power(W)	10W
Optimum Power Voltage(Vmp)	17.56V
Optimum Operating Current(Imp)	0.58A
Open Circuit Voltage(Voc)	21.35V
Short Circuit Current(Isc)	0.64A

Mechanical Characteristics

Cell Type Mono-crystalline	52x35mm
No of Cell	36 (4x9pcs)
Dimensions	250x370x17mm
Weight	1.2Kg
Front Glass	3.5mm,High Transmission, Low Iron,Tempered Glass
Junction box	IP65 Rated
Output Cable	TUV 1x4.0mm ² /UL12AWG,Length:900mm

Temperature and Coefficients

Operating Temperature(°C):	-40°C ~ + 85°C
Maximum System Voltage:	600V(UL)/1000V(IEC) DC
Maximum Rated Current Series:	15A
Temperature Coefficients of Pmax:	-0.47%

Temperature Coefficients of Voc: -0.389%

Temperature Coefficients of Isc: 0.057%

Nominal Operationg Cell Temperature (NOCT): 47+/-2°C

Materials of solar panel

- 1).Solar Cell-----Mono-crystalline solar cell 52*35mm
- 2).Front Glass-----3.2mm, high transmission, low iron, tempered glass
- 3).EVA-----excellent anti-aging EVA
- 4).TPT-----TPT hot seal made of flame resistance
- 5).Frame-----anodized aluminum profile
- 6).Junction Box-----IP65 rated, high quality, with diode protection

Superiority: high quality anodized aluminum frame, high efficiency long life, easy installation, strong wind resistance, strong hail resistance.

Features

1. High cell efficiency with quality silicon materials for long term output stability
2. Strictly quality control ensure the stability and reliability, totally 23 QC procedures
3. High transmittance low iron tempered glass with enhanced stiffness and impact resistance
4. Both Poly-crystalline and Mono-crystalline
5. Excellent performance in harsh weather
6. Outstanding electrical performance under high temperature and low irradiance

Quality assurance testing

Thermal cycling test

Thermal shock test

Thermal/Freezing and high humidity cycling test

Electrical isolation test

Hail impact test

Mechanical, wind and twist loading test

Salt mist test

Light and water-exposure test

Moist carbon dioxide/sulphur dioxide

