
Sunny Apex

30W Photovoltaic Solar Module

EC Series

- Sunny Apex's EC series solar modules ranged from 10Watt to 200Watt
- Using high quality multi-crystalline cells and encapsulation materials
- Anodized aluminum improving corrosion resistance
- Excellent low light behaviour for improved energy yield





Electrical Specifications

Model Type	SA-EC30
Peak Power (Pmax)	30W
Module Efficiency	11.20%
Maximum Power Voltage (Vmp)	17.4V
Maximum Power Current (Imp)	1.72A
Open Circuit Voltage (Voc)	21.9V
Short Circuit Current (Isc)	1.93A
Power Tolerance	-5% / + 10%
Maximum System Voltage	600V
Norminal Operating Cell Temp.	46 °C (+/-2)

Mechanical Specifications


Cell type	Poly-crystalline
Number of cells	36 cells in series
Weight	3.38kg [7.45lbs]
Dimensions	770 x 349 x 25mm
	[30.34 x 13.75 x 0.99in]
Frame	> 15 _u m clear anodized aluminum
Junction Box	JX80B (IP65 waterproof)
Cables	4.00mm ² , 500mm
Connectors	LJQ-1 (MC4 compatible)


Temperature Coefficients

Power	-0.43 %/K
Current	+0.06 %/K
Voltage	-0.36 %/K

Warranties & Certifiations

Warranties	s 2 years product warranty, 20 years limited power	
	warranty of 80% of the mnimum specificed power rating	
Caution: Pead 9	Safety and Installation Instruction before using this product	





Unit: mm [inch]

Note: All electrical parameters are rated at standard test conditions (irradiance of 1000W/m², AM 1.5G, cell temperature 77°F/25°C)

2013 Sunny Apex Development Ltd. All right reserved. Specifications included in this datasheet are subject to change without

Sunny Apex Development Limited

www.sunnyapex.com