

Sterling SS MONO 260 – Silver

| ELECTRICAL CHARACTERISTICS | | SS MONO 260 |
|---|--|-------------|
| <i>Performed at STC: Irradiance 1000 W/m², module temperature 25°C, spectrum at air-mass AM 1.5</i> | | |
| Nominal power @ STC (P _{MAX}) | | 260 W |
| Tolerance (P _{MAX}) | | ± 3% |
| Voltage @ maximum power point (V _{MPP}) | | 30.7 V |
| Current @ maximum power point (I _{MPP}) | | 8.2 A |
| Open circuit voltage (V _{OC}) | | 37.85 V |
| Short circuit current (I _{SC}) | | 8.8 A |
| Module efficiency (Percent) | | 15.9% |
| Temperature coefficient of P _{MPP} (γ ₂) | | -0.44%/K |
| Temperature coefficient of V _{OC} (β ₂) | | -0.32%/K |
| Temperature coefficient of I _{SC} (α ₂) | | 0.058%/K |
| <i>Electrical Data at Nominal Operating Cell Temperature (NOCT) Irradiance 800 W/m², air temperature 20°C, air-speed 1.5 m/s</i> | | |
| Nominal power @ NOCT (P _{MAX}) | | 172 W |
| Voltage @ maximum power point (V _{MPP}) | | 27.1 V |
| Current @ maximum power point (I _{MPP}) | | 6.4 A |
| Open circuit voltage (V _{OC}) | | 34.0 V |
| Short circuit current (I _{SC}) | | 6.9 A |
| Tolerance | | ± 10% |
| Nominal operating cell temperature (NOCT) | | 51.5°C |

| MECHANICAL PARAMETERS | |
|--------------------------------|------------------------|
| Overall dimensions (frame) | 1,663 x 997 x 35 mm |
| Mass | 19 +/- 1 kg |
| Tested static back load (1 h) | 2,400 N/m ² |
| Tested static front load (1 h) | 5,400 N/m ² |

| KEY COMPONENTS | |
|--------------------|--|
| Glass | 3.2 mm thick Solar Glass |
| Photovoltaic cells | Monocrystalline 3BB 156mmx156mm |
| Cell connector | Gebauer & Griller Sn62Pb36Ag2, 2.0x0.17mm |
| Encapsulant | Bridgestone 'Evasky S88' EVA |
| Back sheet | Dunmore 'Dunsolar' PPE+ White |
| Frame | 1.5mm Silver Aluminium anodized |
| Junction Box | TE Connectivity PV4 Connectors, MC4 compatible |

| GENERAL ELECTRICAL PARAMETERS | |
|--|---------|
| Maximum system voltage (V DC) | 1,000 V |
| Maximum module reverse current (I _R) | 18 A |

SUNSOLAR WARRANTY
 All our panels come with a comprehensive performance and workmanship warranty. Linear Power Warranty of 25 years and Product Warranty of 25 years.
 Disclaimer: SunSolar Energy Ltd reserve the right to update specification details without prior notice.



Contact

T: +44 (0) 121 552 8848
 E: sales@sunsolarenergy.co.uk
 W: www.sunsolarenergy.co.uk

SunSolar Energy Limited,
 Houghton Street, Oldbury,
 Birmingham, West Midlands
 B69 2BB

GREAT. BRITISH. ENERGY. Powering a Brighter Future

SunSolar Energy Ltd is a leading British manufacturer of photovoltaic (PV) Solar panels.

- UK's only manufacturer of solar modules
- Superior after sales service
- State-of-the-art technology
- Highest quality components
- 25 year guaranteed performance
- 25 year product warranty
- Quality performance tested using 'Triple A+' flash tester
- MCS and TUV Rheinland approved products
- 100% revenue stays in the UK



For more information, contact us on +44 (0) 121 552 8848
or email sales@sunsolarenergy.co.uk.

www.sunsolarenergy.co.uk