



SP200W-18V/36V POLYCRYSTALLINE

Key features:



PID Free Module:
Anti-PID cell and encapsulation technology
Frameless module requires no module grounding which may PID.



Higher Lifetime Power Yield:
<0.5% annual power degradation
30 year linear power warranty



Saving BOS Cost:
Designed for high voltage systems of up to 1500 VDC, saving BOS cost.



Improved Durability and Reliability:
Dual glass reduces micro-cracking, snail trails, corrosion caused by moisture, sand, salt mist, acid, alkali, etc.




Less Maintenance Requirement:
Reduced soiling and snow coverage requires less maintenance and enhances fire safety.



Aesthetically Pleasing Design:
white back sheet maximizes module efficiency up to 16.84%(60-poly max. output 275W); Transparent back sheet increases light transmission, ideal for installations requiring light to pass through.



Strengthened Mechanical Support:
5400 Pa snow load, 2400 Pa wind load.



Module Models


Electrical Specifications

Model	SP200W-18V/36V
Peak power(Pmax)	200W
Cell Efficiency	16.93%
Max. power volt.(Vmp)	35.8V
Max. power current(Imp)	5.59A
Open circuit volt.(Voc)	44V
Short circuit current(Isc)	6.08A
Power Tolerance	±3%
Max. system voltage	1000V
Series fuse rating(A)	10
Number of bypass diode	6
Operating temperature	-4°C to + 85°C
Maximum system voltage	1000V DC

STC: Irradiance 1000W/m², Module temperature 25°C, AM=1.5

Mechanical Characteristics

Dimensions	1340*990*35mm
Weight	13.5kg
Solar Cells	72 cell in series
Cable	LAPP (4mm ²)
lengths	900mm(-) and 900mm(+)
Connector	Mc4 Plug Type
Glass type	High transmits, Low Iron, 3.2mm Tempered Glass
Frame	Aluminium-alloy



Module Diagram