



# SP20W&10W-18V MONO & POLYCRYSTALLINE

## Key features:



**PID Free Module:**  
Anti-PID cell and encapsulation technology  
Frameless module requires no module grounding which may PID



**Higher Lifetime Power Yield:**  
<0.5% annual power degradation  
30 year linear power warranty



**Saving BOS Cost:**  
Designed for high voltage systems of up to 1000 VDC, saving BOS cost



**Improved Durability and Reliability:**  
Dual glass reduces micro-cracking, snail trails, corrosion caused by moisture, sand, salt mist, acid, alkali, etc.



**Less Maintenance Requirement:**  
Reduced soiling and snow coverage requires less maintenance and enhances fire safety



**Aesthetically Pleasing Design:**  
white back sheet maximizes module efficiency up to 16.84%(60-poly max. output 275W); Transparent back sheet increases light transmission, ideal for installations requiring light to pass through



**Strengthened Mechanical Support:**  
5400 Pa snow load, 2400 Pa wind load



## Module Models

### Electrical Specifications

Model	SP20W-18V	SP10W-18V
Peak power(Pmax)	20W	10W
Cell Efficiency	16.93%	17.04 %
Max. power volt.(Vmp)	17.8V	17.8V
Max. power current(Imp)	1.13A	0.57A
Open circuit volt.(Voc)	21.8V	21.8V
Short circuit current(Isc)	1.23A	0.62A
Power Tolerance	±3%	±3%
Max. system voltage	1000V	1000V
Series fuse rating(A)	12	10
Operating temperature	-4°C to +85°C	
Maximum system voltage	1000V DC	
STC: Irradiance 1000W/m <sup>2</sup> , Module temperature 25°C, AM=1.5		

### Mechanical Characteristics

Dimensions	490*350*25mm	
Weight	1.8kg	
Solar Cells	36 cell in series	
Glass type	High transmits, Low Iron, 3.2mm Tempered Glass	
Frame	Aluminium-alloy	