



285 - 300 Wp 60 MONOCRYSTALLINE CELLS

AEG solar modules combine the most advanced technology with high reliability in manufacture to offer you a product meant for high achievements



HIGH EFFICIENCY WITH PERC TECHNOLOGY

The AEG solar module AS-M605B features PERC coating, which allows you to gain extra efficiency and boost the performances of your solar plant.



FULL BLACK, PREMIUM LOOK

The careful selection of components (cells, backsheet and frames) ensures a premium product look and provides extra aesthetical value.

COMPREHENSIVELY CERTIFIED

AEG solar modules and production facilities are compliant with the the latest standards to guarantee safety and reliability. Production facilities are certified according to ISO 9001, ISO 14001 and OHSAS 18001. AEG solar products are certified among others by:



YOUR ADVANTAGE AT A GLANCE

Premium solar panel with quality components
High efficiency - up to 300 Wp
Product certified IEC 61215, IEC 61730
12 years Product warranty
25 years linear Power warranty



ELECTRICAL CHARACTERISTICS AT STC¹

Nominal Power (Pmax)	[Wp]	285	290	295	300
Tolerance on Nominal Power Pmax ²	[W]	0-5	0-5	0-5	0-5
Maximum Power Voltage (Vmp)	[V]	31.9	32.0	32.1	32.2
Maximum Power Current (Imp)	[A]	8.94	9.07	9.20	9.32
Open Circuit Voltage (Voc)	[V]	38.9	39.2	39.4	39.5
Short Circuit Current (Isc)	[A]	9.56	9.65	9.73	9.84
Module Efficiency (ηm)		17.5%	17.8%	18.1%	18.4%
Maximum System Voltage	[V]	1000	1000	1000	1000
Series Fuse Maximum Rating	[A]	15	15	15	15


ELECTRICAL CHARACTERISTICS NOCT³

Product type: AS-M605B-xxx (xxx=285-300)		285	290	295	300
Maximum Power (Pmax)	[W]	209	212	216	219
Maximum Power Voltage (Vmp)	[V]	29.4	29.6	29.8	30.0
Maximum Power Current (Imp)	[A]	7.11	7.17	7.25	7.30
Open Circuit Voltage (Voc)	[V]	35.8	36.1	36.3	36.5
Short Circuit Current (Isc)	[A]	7.73	7.79	7.86	7.97

MECHANICAL CHARACTERISTICS

Solar cells	60 (6 x 10) monocrystalline silicon, 156.75 x 156.75 mm (6") cells
Front glass	3.2 mm (1.25") high-transparency AR coating glass
Backsheet	black
Encapsulant	EVA (Ethylene-Vinyl Acetate)
Frame	Anodized aluminum alloy, black
Junction box	IP67 rated, 3 bypass diodes
Cables	UVresistant cable, 900 / 1000 mm (35.43" / 39.37"), sec.4.0 mm ²
Connectors	MC4 compatible connectors
Dimensions	1640 mm x 992 mm x 35 mm (64.6" x 39" x 1.37")
Weight	18.5 kg (40.8 lbs)
Maximum load	Wind: 2400 Pa / Snow: 5400 Pa

TECHNICAL DRAWINGS



Modulmaße sind in mm ausgedrückt mit einer Toleranz von +2 mm (+0.079")

Module dimensions in the technical picture are expressed in mm with tolerance +2 mm (+0.079")

1- Standard Test Conditions (STC): Irradiance 1000 W/m², Air Mass AM = 1.5, Cell Temperature 25°C, Power measurement uncertainty within ± 3%.

2- AEG photovoltaic modules are classified according to a principle of positive power tolerance: the Power Output measured at STC of the delivered modules exceeds their assigned Nameplate Nominal Power at STC with a power tolerance range between -0 Wp and +5 Wp.

3 - Normal Operating Cell Temperature (NOCT): Irradiance 800 W/m², Wind Speed 1m/s, Ambient Temperature 20°C, Power measurement uncertainty within ± 3%.

4 - No less than 97% of the minimum 'Peak Power at STC' in the first year; power output decline no more than 0.7% per year (thereafter). Full text of the Warranty Terms available at: www.aeg-industrialsolar.de

© Solar Solutions GmbH. Specifications in this datasheet are subject to change without notice. Code AS-M605B-P-06N1-SBB-285-300 version 20191011EN

AEG is a registered trademark used under license from AB Electrolux (publ).

TEMPERATURE CHARACTERISTICS

NOCT	45°C ± 2°C
Pmax Temp. Coefficient (γ)	-0.40 %/K
Voc Temp. Coefficient (β)	-0.31 %/K
Isc Temp. Coefficient (α)	0.06 %/K
Operating temperature	-40°C to + 85°C

PACKING CONFIGURATION

Packing configuration	30 pcs / pallet
Loading capacity	840 pcs / 40 ft HC

WARRANTIES

Product warranty	12 years
Performance warranty	25 years, linear ⁴

I-V CURVES / IRRADIANCES

Test temperature: 25 °C Module: 285 Wp

