

220 Watt Foldable Solar Panel

The 220 Watt Foldable Solar Panel is lightweight, durable and extremely portable.

The solar panels are mounted to weather resistant fabric that quickly folds for storage and unfolds for use.

Unmatched durability allows for use in the harshest environments and a panel that works even after a portion is damaged.

This compact panel is the perfect accessory to provide power for a wide range of electronics.

The 220 Watt Foldable Solar Panel keeps you connected, powers your outdoor life, and helps you get more out of your outdoor adventures.



Tips For Best Use:

- Angle the solar panel toward the sun for best results.
- Always store in a cool dry environment.
- Not designed for use in the rain.
- Allow time to air dry before packing if the panel is wet.
- Routinely clean the solar panel to ensure best performance.

Benefits Include:

- Compact, lightweight, durable - military tested (MIL-STD-810G).
- Easy to deploy and easy to store.
- Provides some power even in hazy and shaded environments.
- Light sensitive technology turns on early in the day and stays on later in the day.
- Multiple charging adapters to fit your needs and charge a wide range of devices.
- Designed, engineered and manufactured in the United States.

Foldable Charging Capabilities:

Devices:	30 Watt	60 Watt	90 Watt	120 Watt	220 Watt
Cell Phone	✓	✓	✓	✓	✓
Tablet	✓	✓	✓	✓	✓
Laptop			✓	✓	✓
Battery (400 Wh)			✓	✓	✓

Certifications:

- CE
- MIL-STD-810G
- RoHS
- Berry Amendment Compliance

PowerFilm[®]

MADE IN THE USA

SOLAR


220 Watt Foldable Solar Panel

Electrical Characteristics

Rated Voltage at Pmax	15.4V
Rated Current at Pmax	14.4A
Open Circuit Voltage	21.9V
Short Circuit Current	18.6A

Physical Characteristics

Part Number	FM16-14400
Folded Dimensions	31.5 x 17.7 x 2.5 inches 800.1 x 449.6 x 63.5 mm
Unfolded Dimensions	172.0 x 57.7 inches 4,368.8 x 1,465.6 mm
Weight	14.0 lbs 6.4 kg




Thermal Characteristics

Temperature Coefficient for Power	- 0.200 (%/C)
Temperature Coefficient for Voltage	- 0.240 (%/C)
Temperature Coefficient for Voc	- 0.300 (%/C)
Temperature Coefficient for Isc	0.109 (%/C)

Standard Colors:
Stealth Black

Custom Colors:
Camouflage
Digicam
Desert Camo
Khaki
Woodland

IV Curve



Connectors

Standard Connector:
Delphi Weatherpack



Custom Connectors:
SAE
4.5 MM Barrel
Anderson Powerpole

