

SOMERA GRAND ULTIMA MAX SILVER

PRELIMINARY DATASHEET
Product Available from January 2020



SUPERIOR PRICE PERFORMANCE

of half-cell improves module output without adding much to the cost



Half-cell generates only half the current, lowering heat production and **LESS HOT SPOT**, increasing module reliability



Low interconnect resistance between the cells **REDUCES POWER LOSS**, increases overall power output



Three separate junction boxes reduce internal resistance and **IMPROVE HEAT DISSIPATION**



QUALITY AND SAFETY

- ◆ 27 years of linear power output warranty **
- ◆ Rigorous quality control meeting the highest standards
- ◆ 100% EL tested to minimise micro crack
- ◆ Certified for salt mist corrosion resistance – severity VI^
- ◆ Excellent anti-PID performance

APPLICATIONS

- ◆ On-grid large scale utility systems
- ◆ On-grid rooftop industrial and commercial systems
- ◆ Rooftop residential systems

TECHNICAL DATA

SOMERA GRAND ULTIMA MAX SILVER

THIS DATASHEET IS APPLICABLE FOR: SOMERA VSMH.75.AAA.05 (AAA=405-425)

Electrical Data^{1,2} All data refers to STC (AM 1.5, 1000 W/m², 25°C)

Peak Power P _{max} (Wp)	405	410	415	420	425
Maximum Voltage V _{mpp} (V)	42.4	42.4	42.6	42.7	42.7
Maximum Current I _{mp} (A)	9.56	9.67	9.74	9.84	9.96
Open Circuit Voltage V _{oc} (V)	51.6	52.1	52.6	52.7	52.8
Short Circuit Current I _{sc} (A)	9.94	9.96	9.97	9.99	10.17
Module Efficiency η(%)	19.59	19.83	20.08	20.32	20.56

1) STC: 1000 W/m² irradiance, 25°C cell temperature, AM1.5g spectrum according to EN 60904-3.
2) Power measurement uncertainty is within +/- 3%

Electrical Parameters at NOCT³

Power (W)	284.5	288.0	291.5	295.0	298.5
V@P _{max} (V)	37.8	37.9	38.1	38.1	38.1
I@P _{max} (A)	7.52	7.60	7.66	7.74	7.83
V _{oc} (V)	46.3	46.8	47.2	47.4	47.4
I _{sc} (A)	7.78	7.80	7.81	7.82	7.97

3) NOCT irradiance 800 W/m², ambient temperature 20°C, wind speed 1 m/sec

Temperature Coefficients (Tc)

permissible operating conditions

Tc of Open Circuit Voltage (β)	- 0.28%/°C
Tc of Short Circuit Current (α)	0.057%/°C
Tc of Power (γ)	-0.39%/°C
Maximum System Voltage	1500 V
NOCT	45°C ± 2°C
Temperature Range	-40°C to + 85°C

Mechanical Data

Length × Width × Height	2065 × 1001 × 40mm (81.29 × 39.40 × 1.57 inches)
Weight	22.6 kg (49.82 lbs)
Junction Box	IP68/IP67, Split Junction Box with individual bypass diodes
Cable & Connectors	1200 mm (47.24 inches) length cables, MC4 compatible/MC4 connectors
Application Class	Class A (Safety class II)
Superstrate	3.2 mm (0.13 inches) high transmission low iron tempered glass, AR coated
Cells	75 Mono PERC (150 half-cells), 5BB solar cells
Cell Encapsulant	EVA (Ethylene Vinyl Acetate)
Back Sheet	Composite film
Frame	Anodized aluminium frame with twin wall profile
Mechanical Load Test	2400 Pa (Snow load), 2400 Pa (Wind load)
Maximum Series Fuse Rating	20 A


Warranty and Certifications

Product Warranty**	10 years
Performance Warranty**	Linear Power Warranty for 27 years with 3% for 1st year degradation and 0.65% from year 2 to year 27
Approvals and Certificates^	UL1703, IEC 61215:2016, IEC 61730:2016, IEC 61701, IEC 62716, IEC 60068-2-68*, IEC 62804, CE, IS14286, CEC(Californian), IS/IEC 61730


Packaging Information

Quantity /Pallet: 26	Pallets/Container (40'HC): 22	Quantity/Container (40'HC): 572
----------------------	-------------------------------	---------------------------------

Dimensions in mm




Typical Electrical Curves⁴



⁴ Average relative efficiency reduction of 5% at 200 W/m² according to EN 60904-1.

Performance Warranty



^ All (*) certifications under progress.

** Refer to Vikram Solar's warranty document for terms and conditions.

CAUTION: READ SAFETY AND INSTALLATION MANUAL BEFORE USING THE PRODUCT.

Specifications included in this datasheet are subject to change without notice. Electrical data without guarantee. Please confirm your exact requirement with the company representative while placing your order.

*Vikram Solar & Somera are Trademarks of Vikram Solar Limited registered in India.