


S83 sol Premium

320 - 330W



QUALITY SIGNED AND SEALED



ALL BLACK FINISHING BIPV SOLUTION

**98% OF NOMINAL POWER GUARANTEED
IN THE FIRST TWO YEARS**

FULL PACKAGE: MODULES + FLASHINGS



PID FREE

PID tested with excellent results
under the harshest conditions



25 YEARS PRODUCT GUARANTEE



**25 YEARS LINEAR PERFORMANCE
WARRANTY**



CRAFTED WITH PASSION



HIGH RELIABILITY

all modules are checked with high
resolution electroluminescence
measurements.
100% of diodes are tested.

aleo solar module S83 sol Premium

ELECTRICAL DATA (STC)		S83T320	S83T325	S83T330
Rated power	P_{MPP} [W]	320	325	330
Rated voltage	V_{MPP} [V]	32.8	33.0	33.3
Rated current	I_{MPP} [A]	9.75	9.85	9.93
Open-circuit voltage	V_{OC} [V]	40.3	40.5	40.7
Short-circuit current	I_{SC} [A]	10.22	10.31	10.39
Efficiency	η [%]	17.4	17.6	17.9

Electrical values measured under standard test conditions (STC): 1000 W/m²; 25°C; AM 1.5

ELECTRICAL DATA (NMOT)		S83T320	S83T325	S83T330
Power	P_{MPP} [W]	236	240	244
Voltage	V_{MPP} [V]	30.4	30.6	30.8
Current	I_{MPP} [A]	7.78	7.85	7.92
Open-circuit voltage	V_{OC} [V]	37.7	37.9	38.0
Short-circuit current	I_{SC} [A]	8.24	8.31	8.37
Efficiency	η [%]	16.0	16.3	16.5

Electrical values measured under nominal operating conditions of cells: 800 W/m²; 20°C; AM 1.5; wind 1 m/s; Module temperature NMOT: 45,5°C

ELECTRICAL DATA (LOW IRRADIANCE)		S83T320	S83T325	S83T330
Power	P_{MPP} [W]	62	63	64


Electrical values measured under: 200 W/m²; 25°C; AM 1,5

TEMPERATURE COEFFICIENTS			
Temperature coefficient I_{SC}	$\alpha (I_{SC})$	[%/K]	+0.05
Temperature coefficient V_{OC}	$\beta (V_{OC})$	[%/K]	-0.29
Temperature coefficient P_{MPP}	$\gamma (P_{MPP})$	[%/K]	-0.40

BASIC DATA JUNCTION BOX			
Length x width x height	[mm]	148 x 123 x 27	
IP class		IP67	
Cable length	[mm]	1200 (+), 800 (-)	
Connectors		MC4	
Bypass diodes		3	

CLASSIFICATION	S83T320	S83T325	S83T330
Classification range (positive classification) [W]	0/+4.99	0/+4.99	0/+2.99

DIMENSIONS [mm]



BASIC MODULE DATA		
Length x width x height	[mm]	1048 x 1759 x 36 (grid dimension 1016 x 1741)
Weight	[kg]	19,5
Number of cells		60
Cell size	[mm]	158.75 x 158.75
Cell material		Monocrystalline Si, PERC
Number of bus bars		5
Front sheet		Solar glass (TSG)
Back sheet		Polymer sheet, black
Frame material		Al alloy, black


CERTIFICATIONS AND WARRANTY	
Product Guarantee	25 years
Power Guarantee	25 years – linear
Fire Resistance	Class C
Protection Against Electric Shock	II
Certifications	§ IEC 61215, IEC 61730 § IEC 62716 – Ammonia Resistance § IEC 61701 – Salt mist Resistance § IEC 62804 – PID Resistance

LOADS		
Max. module pressure load (Testload)	[Pa]	5400 ¹
Max. module pressure load (Designload) ²	[Pa]	3600 ¹
Max. module suction load (Testload)	[Pa]	2400 ¹
Max. module suction load (Designload) ²	[Pa]	1600 ¹
Max. system voltage	[V _{oc}]	1000
Reverse current load	I_R [A]	20

Mechanical load acc. to IEC/EN 61215:2016
¹ Please observe the mounting conditions in the installation manual
² Testload/ Safety factor 1.5 = Designload

Measurement tolerance of P_{MPP} under STC -3/+3% |
 Accuracy of other electrical values -10/+10%
 Efficiency relating to gross module area

PERFORMANCE GUARANTEE



PLEASE CONTACT YOUR AUTHORISED ALEO DEALER

ALEO SOLAR GMBH
 Marius-Eriksen-Straße 1
 17291 PRENZLAU
 GERMANY

CONTACT
 +49 3984-8328-0
 info@aleo-solar.de
 www.aleo-solar.com

©aleo solar GmbH 11/2019

aleo