




IGNITE THE POWER OF NATURE

Polycrystalline Module --small size 60Watt

Model (RD60TU-18P) Specifications

Electrical Data

Maximum Power(W)	60W
Optimum Power Voltage(Vmp)	19.01V
Optimum Operating Current(Imp)	3.16A
Open Circuit Voltage(Voc)	22.61V
Short Circuit Current(Isc)	3.38A
Cell Efficiency	17.30%
Module Efficiency	13.71%
Tolerance Wattage	0~+3%
NOCT	47°C +/-2°C



Benefits

- High efficiency solar cells with high transmission and textured glass are delivering high efficiency for modules;
- Bypass diode minimizes the power drop caused by shade;
- Tempered glass, EVA resin, and weatherproof film, plus aluminum frame for extended outdoor use;
- Modules independently tested to ensure conformance with certification and regulatory standards;
- Manufacturing facility certified to ISO 9001 quality management system standards.

Modules sorted by current, optimizing system power generation

High Efficiency

Stable Power <math>< 1\%</math>

Low Carbon Emission

Excellent Weather Resistance

Applications

- On-grid residential roof-tops
- On-grid commercial/industrial roof-tops
- Solar power stations
- Other on-grid applications

Temperature Coefficients

Temperature Coefficients of Isc(%)/°C	+0.04
Temperature Coefficients of Voc(%)/°C	-0.38
Temperature Coefficients of Pm(%)/°C	-0.47
Temperature Coefficients of Im(%)/°C	+0.04
Temperature Coefficients of Vm(%)/°C	-0.38



IGNITE THE POWER OF NATURE

Polycrystalline Module --small size 60Watt

Components & Mechanical

Solar Cell	156*63 Poly
Number of Cell(pcs)	4*9
Size of Module(mm)	655*668*35
Front Glass Thickness(mm)	3.2
Surface Maximum Load Capacity	2400-5400Pa
Allowable Hail Load	23m/s ,7.53g
Weight Per Piece(KG)	5.2
Bypass Diode Rating(A)	10
Frame(Material Corners,etc.)	35#
Temperature Range	-40°C to +85°C
FF (%)	70-76%
Standard Test Conditions	AM1.5 1000W/m ² 25°C


Packing

Packing	Wooden Box
Pieces per container	60pcs/Pallets

Project Picture



Engineering Drawings



©2016 NINGBO RENELED NEW ENERGY CO.,LTD. All rights reserved.
Specifications included in this datasheet are subject to change without notice.



NINGBO RENELED NEW ENERGY CO.,LTD.
ADD: No. 35 Jintong Road, Binhai Industrial Park,
Xiangshan County, Ningbo, 315700, China
TEL: 0086 (0)574 65893072
FAX: 0086 (0)574 65786317