

# MONOCRYSTALLINE 60M



GERMAN-based company

- ◆ TT285-60M 285 Wp ◆ TT295-60M 295 Wp
- ◆ TT290-60M 290 Wp ◆ TT300-60M 300 Wp



## High Conversion Efficiency

High panel efficiency to guarantee high power output



## Self-Cleaning And Anti-Reflection Glass

Coating glass for self-cleaning reduces surface dust



## Outstanding Low Irradiation Glass

Outstanding panel performance even in weak light conditions



## Excellent Durability


Wind load up to 2400 Pa, Snow load up to 5400 Pa



## 0~+5W Positive Power Tolerance



## Easy Installation



25 Year Performance Warranty



12 Year Material and Workmanship Warranty



IEC 61215, IEC 61730  
IEC 61701  
IEC 62716  
IEC 6006-2-68  
TS EN 13501-5

Model Type	TT285 60M	TT290 60M	TT295 60M	TT300 60M
Peak Power (Pmax)	285 Wp	290 Wp	295 Wp	300 Wp
Module Efficiency	17,38	17,69	17,99	18,30
Maximum Power Voltage (Vmp)	32,77	32,92	33,21	33,42
Maximum Power Current (Imp)	8,73	8,84	8,92	9,02
Open Circuit Voltage (Voc)	38,46	38,68	38,82	38,95
Short Circuit Current (Isc)	9,24	9,36	9,44	9,54
Power Tolerance	0~+5W			
Maximum System Voltage	1000V DC			
Nominal Operating Cell Temp.	-40 ~ +85°C			
Fire Safety	Class C			
Maximum Series Fuse Rating	15A			

### MECHANICAL SPECIFICATIONS

Cell Dimensions	156,75 mm x 156,75 mm
Cells per Module	60 (6X10)
Weight	18 kg
Panel Dimensions	1648x995x35mm
Panel Dimensions (Optional)	1640x990x35mm
Max. Wind/Snow Load	2400/5400 Pa
Junction Box	IP67

### TEMPERATURE CHARACTERISTICS

Temp. Coeff. of (Isc)	0.055%/°C
Temp. Coeff. of (Voc)	-0.29%/°C
Temp. Coeff. of (Pmax)	-0.38%/°C


### PACKING CONFIGURATION

Container	20' GP	40' GP
Pieces per Pallet	31	31
Pieces per Container	372	938



### PHYSICAL CHARACTERISTICS

A (1:4)

Unit: mm



### ELECTRICAL CHARACTERISTICS



\*Note: The specifications are obtained under the standard test conditions: 1000W/m<sup>2</sup> solar irradiance, 1.5 Air Mass and cell temperature of 25°C. The NOCT is obtained under the Test Conditions 800W/m<sup>2</sup> solar radiation, ambient temperature 20°C, wind speed 1m/s. Measurement uncertainty for all panels is 6%. The actual transactions will be subject to the contracts. These parameters are for reference only and it is not a part of the contracts. The specifications are subject to change without prior notice.