

MonoPower Large Half Cells

ASP HM6L-72 Series 420W-435W

Monocrystalline PV-module



QUALITY & RELIABILITY

Best raw materials, optimized production process and accurate testing makes the quality difference



GERMAN ENGINEERING

Best design by the art of German engineering



SAVE INVESTMENT

Product warranty of 12 years and performance warranty of 25 years



POSITIVE PERFORMANCE TOLERANCE

Up to +5 W plus-tolerance on output




FOR ALL ENVIRONMENTAL CONDITIONS

Resistant against PID, sand, salt and ammonia



STABLE AND STRONG

Capable to bear heavy snow loads up to 5400 Pa and wind loads up to 2400 Pa




12 YEARS
PRODUCT WARRANTY

OUR PERFORMANCE GUARANTEE



25 YEARS
PERFORMANCE GUARANTEE




CERTIFICATES



IEC 61215
IEC 61730
PERIODICAL
INCEPTION



PID RESISTANT
SALT MIST RESISTANT
SAND RESISTANT
CORROSIVE GAS (NH₃)



ALPHA SOLAR PLANET
Enjoy the quality difference

MonoPower Large Half Cells

ASP HM6L-72 Series 420W-435W

TECHNICAL DATA

		ASP420HM6L-72	ASP425HM6L-72	ASP430HM6L-72	ASP435HM6L-72
Maximum power	Pmax (Wp)	420	425	430	435
Maximum power voltage	Vmp (V)	40.2	40.4	40.6	40.8
Maximum power current	Imp (A)	10.45	10.52	10.60	10.67
Open-circuit voltage	Voc (V)	48.8	49.0	49.2	49.4
Short-circuit current	Isc (A)	11.04	11.11	11.19	11.26
Module efficiency	%	18.9	19.1	19.3	19.6
Power tolerance	Pmax (W)		0/+5		
Maximum system voltage DC	V		1500		
Operating temperature	°C		-40 to +85		
Temperature coefficients of Pmax	%/°C		-0.370		
Temperature coefficients of Voc	%/°C		-0.286		
Temperature coefficients of Isc	%/°C		0.057		
Nominal operating cell temp. (NOCT)	°C		45±2		

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.


MATERIAL CHARACTERISTICS

Cell type	Monocrystalline 166 x 83 mm
No. of cells	144 (6 x 24)
Dimensions	2115 x 1052 x 40 mm
Weight	24 kg
Junction box	IP 68 rated
Output cable	4.0 mm ² , 350 mm length
Connector type	MC 4/MC 4 compatible
Hail resistance	Max. Ø 25 mm, at 23 m/s
Wind load	2400 Pa/244 kg/m ²
Mechanical load	5400 Pa/550 kg/m ²

PACKING INFORMATION

Packing configuration	56 pcs/double pallet
Loading capacity	616 pcs/40 HQ
Size / pallet	2150 x 1140 x 2344 mm
Weight	1466 kg/double pallet

DRAWINGS



Alpha Solar Planet GmbH
Schwalbenweg 1 g, 86343 Königsbrunn
Germany

Tel.: +49 8231 99190 70
Fax: +49 8231 99190 89

E-mail: sales@a-s-p.solar
Web: www.a-s-p.solar

