



	<b>F-1500-12-70</b>	<b>F-1500-24-40</b>	<b>F-3000-12-100</b>	<b>F-3000-24-70</b>
Continuous output power FTS	1500 W	1500 W	3000 W	3000 W
Output power surge (1 sec.)	3000 W	3000 W	6000 W	6000 W
Output Voltage	230VAC or 110VAC	230VAC or 110VAC	230VAC or 110VAC	230VAC or 110VAC
THD max.	±3%	±3%	±3%	±3%
Output wave form	Pure sine wave	Pure sine wave	Pure sine wave	Pure sine wave
Frequency	50Hz or 60Hz ±0.05%	50Hz or 60Hz ±0.05%	50Hz or 60Hz ±0.05%	50Hz or 60Hz ±0.05%
Input Voltage	10.5 to 15 VDC	21 to 30 VDC	10.5 to 15 VDC	21 to 30 VDC
Max. Efficiency	90%	90%	90%	90%
Sleep consumption	<5mA	<5mA	<5mA	<5mA
Transfer rate	<10 ms	<10 ms	<10 ms	<10 ms
Input voltage	190-250VAC or 90-130VAC	190-250VAC or 90-130VAC	190-250VAC or 90-130VAC	190-250VAC or 90-130VAC
Efficiency	90%	90%	90%	90%
Output Current	70 ADC	40 ADC	100 ADC	70 ADC
Adjustable output current	yes	yes	yes	yes
IP class	IP 21	IP 21	IP 21	IP 21
Dimensions incl. term.	335x200x106mm 12.2x7.9x4.4in	335x200x106mm 12.2x7.9x4.4in	422x200x106mm 16.6x7.9x4.4in	422x200x106mm 16.6x7.9x4.4in
Weight	6kg or 13.2lbs	6kg or 13.2lbs	8kg or 17.6lbs	8kg or 17.6lbs