



GE4ALL
Engelandlaan 22
2391 PN Hazerswoude dorp
The Netherlands

+31 172 404 195
+31 172 239 944
info@ge4all.eu
www.ge4all.eu

Model SG5K-B, SG6K-B



Model SG5K-B, SG6K-B	
Parameter	Value
Isolation type	Transformer
Recommended maximum power of PV array	5500WP/6600WP
Maximum array open-circuit voltage	780Vdc
Maximum power point (MPPT) scope of PV	300~650Vdc / 320~650Vdc
Type of connection type between inverter & PV array	Water-proof direct-plug terminals
Number of parallel PV array strings that can be connected to the inverter	4
Maximum array input current	20A
Rated AC output power	5.000W / 6.000W
Current THD	<3% (at nominal power)
Power factor	>0.99 (at nominal power)
Maximum efficiency	94%
European efficiency	93%
Nominal grid voltage	180~260VAC
Nominal grid frequency	50 & 60 Hz
Power consumption idle mode (f.e. during the night)	<0.5W
Communication interface	RS-485, optional ethernet/GPRS
Protection class	IP65 (outdoor)
Operating temperature	-25°C ~ +60°C
Noise	<40dB
Cooling	Forced air cooling
Size (W x H x D)	410 x 580 x 283 mm
Weight	65 kg