

Specifications 规格:						
model 型号	PN-P-1500w					
input voltage 输入电压	DC12V					
input voltage range 输入电压范围	11-15V					
efficiency 效率	85%					
output voltage 输出电压	AC220V					
continuous power 运行功率	1500W					
peak power 峰值功率	3000W					
output wave 输出波形	pure sine wave 纯正弦波					
output frequency 输出频率	50Hz					
environment 环境:						
environment temperature 环境温度	-5° C ~ +40° C					
relative humidity 相对湿度	10% ~ 90% RH					
storage temperature 存放温度	-20° C ~ +50° C					
storage humidity 存放湿度	5% ~ 95% RH					
cooling mode 冷却方式	cooling by fan 冷却风扇					
protection 保护:						
low voltage alarm 低电压报警	10.2-10.8v					
low voltage protection 低电压保护	9.2-9.8v					
overload protection 过载保护	120%~130%					
over voltage protection 过压保护	15-16v					
over temperature protection 防过热装置	shut down 关闭					
short circuit protection 短路保护	shut down 关闭					
packing details 包装细节:						
shape size 外形尺寸	364*199*73MM					
carton size 纸箱尺寸	41*23.5*13.5CM					
net weight 净重	4.3 KG					
gross weight 毛重	4.9 KG					
socket	select your socket					
A	B	C	D	E	F	G