

**Features:**

- True sine wave output(THD < 3%)
- Input & output fully isolation
- Load control cooling fan
- Advanced microprocessor
- Input polarity reverse/under voltage/over voltage protections
- Output short circuit/overload/over temperature protections
- LED indicators display Power & failure status
- Warranty: 2 Years



Model		CK150-112	CK150-124	CK150-148	CK150-212	CK150-224	CK150-248			
Input	DC voltage	12V	24V	48V	12V	24V	48V			
	Voltage range	10-16VDC	20-33VDC	40-63VDC	10-16VDC	20-33VDC	40-63VDC			
	No load current draw	< 0.6A								
	Efficiency	> 89%	> 89%	> 90%	>90%	>90%	> 91%			
	DC connection	Cables With Clips or Car Adaptor								
Output	AC voltage	100/110/120VAC			220/230/240 VAC					
	Continuous power	150W								
	Surge power	300W								
	Waveform	Pure sine wave								
	Frequency	50Hz or 60Hz								
	AC regulation	±3%								
Protection	Low voltage alarm	10.5DC±0.5V	21DC±1V	42VDC±1V	10.5DC±0.5V	21DC±1V	42VDC±1V			
	Low voltage shut down	10DC±0.5V	20DC±1V	40VDC±1V	10DC±0.5V	20DC±1V	40VDC±1V			
	Over load	Shut Down								
	Over voltage shut down	16V	33V	63V	16V	33V	63V			
	Over thermal	Shut Down automatically								
Environment	Working temperature	-10°C and +50°C								
	Working humidity	20% ~ 90%RH								
	Storage temperature	-30°C and +70°C								
Package	Machine size(mm)	180*105*60								
	Packing size(mm)	275*160*114								
	Net weight(kg)	0.86								
	Gross weight(kg)	1.13								
	Packing	Carton								
Other	Start	Soft start								
	Cooling ways	Intelligent cooling fan								
	Application	Home and Office appliances, Power tools and Portable equipments, Vehicle, Yacht and Solar power systems...etc.								