

Features:

- True sine wave output(THD < 3%)
- Input & output fully isolation
- Load control cooling fan
- Advanced microprocessor
- Input polarity reverse/under voltage/over voltage protections
- Output short circuit/overload/over temperature protections
- LED indicators display Power & failure status
- Warranty: 2 Years



Model		CK1500-112	CK1500-124	CK1500-148	CK1500-212	CK1500-224	CK1500-248			
Input	DC voltage	12V	24V	48V	12V	24V	48V			
	Voltage range	10-16VDC	20-33VDC	40-63VDC	10-16VDC	20-33VDC	40-63VDC			
	No load current draw	< 0.8A								
	Efficiency	> 88%	> 89%	> 89%	> 89%	> 89%	> 90%			
	DC connection	Cables With Clips or Car Adaptor								
Output	AC voltage	100/110/120VAC			220/230/240 VAC					
	AC voltage	100/110/120VAC			220/230/240 VAC					
	Continuous power	1500W								
	Surge power	3000W								
	Waveform	Pure sine wave								
	Frequency	50Hz or 60Hz								
Protection	AC regulation	±3%								
	Low voltage alarm	10.5DC±0.5V	21DC±1V	42VDC±1V	10.5DC±0.5V	21DC±1V	42VDC±1V			
	Low voltage shut down	10DC±0.5V	20DC±1V	40VDC±1V	10DC±0.5V	20DC±1V	40VDC±1V			
	Over load	Shut Down								
	Over voltage shut down	16V	33V	63V	16V	33V	63V			
Environment	Over thermal	Shut Down automatically								
	Working temperature	-10°C and +50°C								
	Working humidity	20% ~ 90%RH								
Package	Storage temperature	-30°C and +70°C								
	Machine size(mm)	385*165*85								
	Packing size(mm)	470*230*148								
	Net weight(kg)	3.8								
	Gross weight(kg)	4.6								
Other	Packing	Carton								
	Start	Soft start								
	Cooling ways	Intelligent cooling fan								
Application			Home and Office appliances, Power tools and Portable equipments, Vehicle, Yacht and Solar power systems...etc.							