

Features:

- True sine wave output(THD < 3%)
- Input & output fully isolation
- Load control cooling fan
- Advanced microprocessor
- Input polarity reverse/under voltage/over voltage protections
- Output short circuit/overload/over temperature protections
- LED indicators display Power & failure status
- USB 5V Output
- Input 96VDC,110VDC Optional
- Warranty: 2 Years



Model		CH700-112	CH700-124	CH700-148	CH700-212	CH700-224	CH700-248
Input	DC voltage	12V	24V	48V	12V	24V	48V
	Voltage range	10-15.5VDC	20-30VDC	40-60VDC	10-15.5VDC	20-30VDC	40-60VDC
	No load current draw	< 0.58A	< 0.22A	< 0.15A	< 0.6A	< 0.2A	< 0.15A
	Efficiency	> 89%	> 89%	> 90%	>90%	>90%	> 91%
	DC connection	Cables					
Output	AC voltage	100/110/120VAC			220/230/240 VAC		
	Continuous power	700W					
	Surge power	1400W					
	Waveform	Pure sine wave					
	Frequency	50Hz or 60Hz					
	AC regulation	±3%					
Protection	Low voltage alarm	10.5DC±0.5V	21DC±1V	42VDC±1V	10.5DC±0.5V	21DC±1V	42VDC±1V
	Low voltage shut down	10DC±0.5V	20DC±1V	40VDC±1V	10DC±0.5V	20DC±1V	40VDC±1V
	Over load	Shut Down					
	Over voltage shut down	15.5V±1V	30V±1V	60V±1V	15.5V±1V	30V±1V	60V±1V
	Over thermal	Shut Down automatically					
Environment	Working temperature	-10°C and +50°C					
	Working humidity	20% ~ 90%RH non-condensing					
	Storage temperature	-30°C ~ 70°C					
Package	Machine size(mm)	260*140*65					
	Packing size(mm)	310*170*110					
	Net weight(kg)	1.2					
	Gross weight(kg)	1.5					
	Packing	Carton					
Other	Start	Soft start					
	Cooling ways	Intelligent cooling fan					
	Application	Home and Office appliances, Power tools and Portable equipments,Vehicle, Yacht and Solar power systems...etc.					