

**Features:**

- True sine wave output(THD < 3%)
- Input & output fully isolation
- Load control cooling fan
- Advanced microprocessor
- Input polarity reverse/under voltage/over voltage protections
- Output short circuit/overload/over temperature protections
- LED indicators display Power & failure status
- USB 5V Output
- Input 96VDC,110VDC Optional
- Remote Control RJ-12
- Warranty: 2 Years



Model		CH2000-112	CH2000-124	CH2000-148	CH2000-212	CH2000-224	CH2000-248			
Input	DC voltage	12V	24V	48V	12V	24V	48V			
	Voltage range	10-15.5VDC	20-30VDC	40-60VDC	10-15.5VDC	20-30VDC	40-60VDC			
	No load current draw	< 0.7A	< 0.5A	< 0.25A	< 0.7A	< 0.5A	< 0.25A			
	Efficiency	> 89%	> 89%	> 90%	>90%	>90%	> 91%			
	DC connection	Cables								
Output	AC voltage	100/110/120VAC			220/230/240 VAC					
	Continuous power	2000W								
	Surge power	4000W								
	Waveform	Pure sine wave								
	Frequency	50Hz or 60Hz								
	AC regulation	±3%								
Protection	Low voltage alarm	10.5DC±0.5V	21DC±1V	42VDC±1V	10.5DC±0.5V	21DC±1V	42VDC±1V			
	Low voltage shut down	10DC±0.5V	20DC±1V	40VDC±1V	10DC±0.5V	20DC±1V	40VDC±1V			
	Over load	Shut Down								
	Over voltage shut down	15.5V±1V	30V±1V	60V±1V	15.5V±1V	30V±1V	60V±1V			
	Over thermal	Shut Down automatically								
Environment	Working temperature	-10°C and +50°C								
	Working humidity	20% ~ 90%RH non-condensing								
	Storage temperature	-30°C ~ 70°C								
Package	Machine size(mm)	375*235*98								
	Packing size(mm)	480*290*175								
	Net weight(kg)	4.0								
	Gross weight(kg)	5.0								
	Packing	Carton								
Other	Start	Soft start								
	Cooling ways	Intelligent cooling fan								
	Application	Home and Office appliances, Power tools and Portable equipments, Vehicle, Yacht and Solar power systems...etc.								