

# RECon 75HV Line @ 630V

RECon 75HV @ 630V -		780	1560	2340
<b>Input (DC)</b>				
Suggested DC power	kWp	995	1990	2985
Max. input current	A	850	1700	2550
Max. input voltage in open circuit	V		1500	
MPPT range	V		945-1300	
Number of MPPT trackers	-		1	
<b>Output (AC)</b>				
Rated output voltage	V		630	
Frequency	Hz		50 / 60	
Rated power@50°C	kW	819	1638	2457
Rated current@50°C	A	750	1500	2250
Power factor - rated	-		> 0,99 at rated power	
Total harmonic distortion	%		< 3	
<b>Auxiliary power</b>				
Auxiliary supply from UPS	-		230V	
Auxiliary supply voltage range	-		195 – 253V	
Standby consumption	W	75	150	225
<b>Efficiency</b>				
Maximum efficiency	%		98.6	
Euro Efficiency	%		98.4	
CEC Efficiency	%		98.2	
<b>Mechanical details</b>				
Dimensions (WxHxD)	mm	2700x2200x900	3700x2200x900	4700x2200x900
Weight	kg	1200	1800	2500
Protection class	-		IP 20 / IP54 for Outddor	
Colour	-		RAL 7035	
<b>Ambient Conditions</b>				
Operating temperature range	°C		10 ÷ + 60°C	
Maximum Operating Altitude	m		2000 (without derating)	
Maximum Relative Humidity	%		95 (without condensing)	
Noise emission @ 1m/10m (1)	dB		78/58	
<b>Other Features</b>				
Cooling System	-		Forced Air	
Array grounding configuration	-		Negative grounded / Positive grounded / Floating	
Array ground fault protection	-		Isolation monitor	
AC side ground fault protection	-		Optional	
Protection against overvoltage (SPD)	-		DC Side: Yes - AC Side: Optional	
Grid Fault monitoring	-		Yes	
Thermal protection	-		Yes	
Nr. of independent AC outputs	-		1	
Maximum Nr. of DC inputs per pole	-	8 + 8	16 + 16	24 + 24
DC input currents monitoring	-		Optional	
AC side disconnection device	-		Yes - Load Break Switch with Fuses	
DC side disconnection device	-		Yes - Load Break Switch	
AC Energy Meter	-		Optional (Class 0,5)	
<b>Interfaces</b>				
Local user interface	-		Touch screen display	
String-Box communication port	-		RS485 Modbus	
PC communication port	-		RS232 - RS485 - USB	
Remote communication port	-		Ethernet	
Communication Protocol	-		Standard Modbus RTU / Modbus TCP	
Power Modulation	-		Yes - via Remote Control/PPC	
<b>Standards &amp; certifications</b>				
Product standard	-		2004/108/EC - 2006/95/EC - CEI EN 62109-1 (2010) - CEI EN 62109-2 (2012) - IEC60730 (2010) - UL1741 (2010) - UL1998 (2008) - CSA C22.2 No. 107.1-01 (2011)	
Grid requirements	-		CEI 0-16 ED. III (2012) - VDE 0126-1-1 (2006) - SAGC2.6 - IEEE1547 (2003) - IEEE1547.1 (2005)	
EMC	-		EN 61000 - 6 - 2 / EN 61000 - 6 - 4 / FCC	
Euro Efficiency	-		IEC 61683: 1999-11	
Power management functions	-		LVRT, Power factor Control, Grid Fault Support, Power / Frequency Control and Ramp Rate	