

USP 3000W/3500W/4000W/5000W/6000W/7000W/8000W/10000W

Model		3000W	3500W	4000W	5000W	6000W	7000W	8000W	10000W	
Input	Rated capacity	3000W	3500W	4000W	5000W	6000W	7000W	8000W	10000W	
Input	peak power	3000W	3500W	4000W	5000W	6000W	7000W	8000W	10000W	
Input	Commercial Power range (VAC)	100/110/120/127/220/230 (+25%, -35%)		100/110/120/127/220/230 (+20%)						
Battery	DC Voltage	24/48VDC		48/96/192VDC			96/192VDC			
Output	AVR voltage range (VAC)	110/120/127/220/230/240±10% (Auto-sensing)		110/120/127/220/230/240 (No Auto-sensing)						
	over voltage protection	30V/60V		60V/120V/240V			120V /240V			
	under voltage protection	21V/42V ±1V		42V/48V/168V ±1V			84V/168V ±1V			
	Transfer time	Typical:5ms (Including detection time)								
Output	waveform	Pure sine wave								
	Frequency	Commercial power supply:shared frequency with the commercial inversion state:60/50±0.5								
Temperature	Operating Temperature	0°C~70°C								
Appearance	External Size(mm) (L*W*H)	470*260*500					550*260*650			
	Gross Size(mm) (L*W*H)	547*345*538 (1PCS)					710*440* (1PCS)			
	Net weight(kg)	40	41	42	43	46	77/78	79/80	81/83	
	Gross weight(kg)	42	43	44	45	47	79/80	81/82	83/85	
protection	overload	IPS automatically shut down if overload exceeds 120% of normal value for 10 seconds, IPS automatically resume work if overload comes to rated load.								
Battery	Type	Sealed, maintenance-free lead acid								
	Recharge current	25A (Maximum)								
	Battery protection	Automatic self-test, discharge protection, over-charge protection, smart management system.								