

Three Phase 17-40kW (New Version)



Features:

- Intelligent control, 20% more DC input, 10% AC over-load ability
- Intelligent real-time monitoring of DC connectors, much safer
- Up to 300V AC output voltage, suitable for unstable grid. Maximum 1100v DC input voltage



Technical Data

Inverter model	ST17KTN	ST20KTN	ST25KTN	ST33KTN	ST36KTN	ST40KTN
Input (DC)						
Max DC power	20.4kW	24kW	30kW	39.6kW	43.2kW	48kW
Max DC voltage	1100V					
Start up voltage	160V					
MPPT voltage range/Rated voltage	200~950V/620V					
Full load MPPT voltage range	450-850V	500-850V	550-850V	500-850V	550-850V	550-850V
Max input current per MPPT	24A+24A		36A+24A	36A+36A		
MPPT tracker/ String per tracker	2/(2+2)		2/(3+2)	2/(3+3)		
Output(AC)						
AC nominal power	17kW	20kW	25kW	33kW	36kW	40kW
Overload capacity	110%					
Nominal AC voltage/frequency	3L/N/PE,220V/380V, 230V/400V, 240V/415V, 50/60Hz/±5Hz					
Max output current	27A	32A	40A	52A	58A	61A
Power factor(Adjustable)	>0.99/0.8 leading~0.8 lagging					
Harmonics(THD)	<2%					
DC injection	<0.5%					
System performance						
Max efficiency	98.40%	98.50%	98.50%	98.60%	98.70%	98.70%
Euro efficiency	98.10%	98.20%	98.20%	98.30%	98.40%	98.40%
MPPT efficiency	99.90%					
Internal consumption(night)	<0.1W					
Electric protection	AC output over-current protection, DC input reverse polarity protection, AC output short circuit protection, AC output over-current protection, Insulation impedance monitoring, Leakage current monitoring, AC and DC surge protection, Anti-islanding protection, Over temperature protection,Over/under voltage & frequency protection.					
Topology structure	Transformerless					
General data						
Net dimension (W*H*D)	685*450*150mm					
Gross dimension (W*H*D)	894*684*300mm					
Net weight/Gross weight	48kg/54kg					
Degree of protection	IP65					
Cooling method	Natural Convection					
Noise(Typical)	<30dBA					
Operation temperature	-25°C~60°C (>45°C Derating) /0~100%(Non-condensing)/4000m (<3000m no derating)					
Humidity and Altitude						
DC connector/AC connector	MC4 or other same kind of plug and play connectors/Waterproof PG connector+OT terminal					
Communication(RS485/WiFi)	Yes/Opt.					
Certificate	To Be Advised					
Warranty (5/10/15 years)	Standard/Opt./Opt.					