

## Three Phase Inverter with Synergy Technology

for the 208V Grid for North America

SE43.2KUS



### Specifically designed to work with power optimizers

- / Easy two-person installation – each unit mounted separately, equipped with cables for simple connection between units
- / Balance of System and labor reduction compared to using multiple smaller string inverters
- / Independent operation of each unit enables higher uptime and easy serviceability
- / No wasted ground area: wall/rail mounted, or horizontally mounted under the modules (10° inclination)
- / Integrated arc fault protection and rapid shutdown for NEC 2014 and 2017, per article 690.11 and 690.12
- / Built-in module-level monitoring with Ethernet or cellular GSM
- / Fixed voltage inverter for superior efficiency (97%) and longer strings
- / Integrated DC Safety Switch and optional surge protection
- / Built-in RS485 Surge Protection, to better withstand lightning events

# Three Phase Inverter with Synergy Technology for the 208V Grid for North America

## SE43.2KUS

SE43.2KUS		
<b>OUTPUT</b>		
Rated AC Power Output	43200	VA
Maximum AC Power Output	43200	VA
AC Output Line Connections	4-wire WYE (L1-L2-L3-N) plus PE or 3 wire Delta	
AC Output Voltage Minimum-Nominal-Maximum <sup>(1)</sup> (L-N)	105-120-132.5	Vac
AC Output Voltage Minimum-Nominal-Maximum <sup>(1)</sup> (L-L)	183-208-229	Vac
AC Frequency Min-Nom-Max <sup>(1)</sup>	59.3 - 60 - 60.5	Hz
Maximum Continuous Output Current (per Phase) @208V	120	A
GFDI Threshold	1	A
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes	
<b>INPUT</b>		
Maximum DC Power (Module STC), Inverter / Unit	58200 / 19400	W
Transformer-less, Ungrounded	Yes	
Maximum Input Voltage DC to Gnd	300	Vdc
Maximum Input Voltage DC+ to DC-	600	Vdc
Nominal Input Voltage DC to Gnd	200	Vdc
Nominal Input Voltage DC+ to DC-	400	Vdc
Maximum Input Current	114	Adc
Maximum Input Short Circuit Current	135	Adc
Reverse-Polarity Protection	Yes	
Ground-Fault Isolation Detection	350kΩ Sensitivity per Unit	
CEC Weighted Efficiency	97	%
Nighttime Power Consumption	< 12	W
<b>ADDITIONAL FEATURES</b>		
Supported Communication Interfaces	RS485, Ethernet, Cellular GSM (optional)	
Rapid Shutdown	NEC2014 and NEC2017 compliant/certified, upon AC Grid Disconnect	
RS485 Surge Protection	Built-in	
<b>DC SAFETY SWITCH</b>		
DC Disconnect	1000V / 3 x 40A	
DC Surge Protection	Optional, Type II, field replaceable	
<b>STANDARD COMPLIANCE</b>		
Safety	UL1741, UL1741 SA, UL1699B, UL1998, CSA 22.2	
Grid Connection Standards	IEEE 1547, Rule 21, Rule 14 (HI)	
Emissions	FCC part15 class A	
<b>INSTALLATION SPECIFICATIONS</b>		
Number of units	3	
AC Output Conduit Size / Max AWG / Max PE AWG	2" / 4/0 / 4	
DC Output Conduit Size / Terminal Block AWG Range / Number of Strings <sup>(2)</sup>	2 x 1.25" / 6-14 / 9 strings	
Dimensions (H x W x D)	Primary Unit: 37 x 12.5 x 10.5 / 940 x 315 x 260; Secondary Unit: 21 x 12.5 x 10.5 / 540 x 315 x 260	in / mm
Weight	Primary Unit: 105.8 / 48; Secondary Unit 99.2 / 45	lb / kg
Operating Temperature Range	-40 to +140 / -40 to +60 <sup>(3)</sup>	
Cooling	Fan (user replaceable)	
Noise	< 60	
Protection Rating	NEMA 3R	
Bracket Mounted (Brackets Provided)		

<sup>(1)</sup> For other regional settings please contact SolarEdge support

<sup>(2)</sup> Single input option per unit (up to 3AWG) available

<sup>(3)</sup> For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note-na.pdf>