

**SG800 Series**


**PV Smart Microinverter**

**SG800 Series**




- Single unit connects up to four PV modules
- Maximum 800W AC output power
- Single-phase output, Flexible 3-phase PV systems
- 2.4G wireless communication and monitoring
- Up to 11 units (230V) per branch
- Customizable various input (DC, PV) voltage range
- Integrated AC bus cable, Ready-To-Use
- Low cost, Easy installation

**Basic Structure**



**Dimensions**



# SG800 Series PV Smart Microinverter - Parameter Table

Product Series	SG800 Series			
Model	SG800MQ (Custom-made)	SG800MD (Custom-made)	SG800HD (Custom-made)	SG800TQ (Custom-made)
<b>Input Data(DC,PV)</b>				
Number of Input MC4 Connector	4 set	2 set	2 set	4 set
MPPT Voltage Range	22V-40V	22V-40V	36V-60V	80V-115V
Operation Voltage Range	18V-50V	18V-50V	30V-70V	70V-120V
Maximum Input Voltage	50V	50V	70V	120V
Startup Voltage	18V	18V	30V	70V
Maximum Input Power	4*200W	2*400W	2*400W	4*200W
Maximum Input Current	4*8A	2*16A	2*11.1A	4*2.5A
<b>Output Data(AC)</b>				
Single-Phase Grid Type	120V & 230V			
Rated Output Power	795W			
Maximum Output Power	800W			
Nominal Output Current	@120VAC : 6.6A / @230VAC : 3.4A			
Nominal Output Voltage	120VAC / 230VAC			
Default Output Voltage Range	@120VAC : 80V-160V / @230VAC : 180V-280V			
Nominal Output Frequency	50Hz / 60Hz			
Default Output Frequency Range	@50Hz : 47.5Hz-52.5Hz / @60Hz : 57.5Hz-62.5Hz			
Power Factor	>0.99			
Total Harmonic Distortion	THD <5%			
Maximum Units per Branch	@120VAC : 6 units / @230VAC : 11 units			
<b>Efficiency</b>				
Peak Efficiency	95%			
CEC Weighted Efficiency	@120VAC : 92.5% / @230VAC : 93.5%			
Nominal MPPT Efficiency	99.9%			
Night Power Consumption	<700mW			
<b>Mechanical Data</b>				
Operating Ambient Temperature Range	-40°C to +65°C			
Storage Temperature Range	-40°C to +85°C			
Dimensions (W x H x D)	250mm x 230mm x 38mm (not include connectors and cable)			
Weight	2.5kg			
Max Current of AC Bus Cable	40A			
Waterproof Grade	IP65			
Cooling Mode	Natural Convection - No Fans			
<b>Other Features</b>				
Communication(Inverter to DataBox)	2.4G Wireless			
Transformer Design	High Frequency Transformers, Galvanically Isolated			
Integrated Ground	Equipment ground is provided by the PE in the AC cable. No additional ground is required.			
Protection Functions	Isolated Island Protection, Voltage Protection, Frequency Protection, Temperature Protection, Current Protection, etc.			
Design Compliance	NB/T32004:2013,NB/T32004:2013,EN61000-3-2,EN62109,VDE0126,UL1741 etc.			


**\*\* Specifications subject to change without notice\*\***

# Installation Schematic

SG800 Series Microinverter

@

Single-Phase 120V




1. SG800 Series @Single-Phase 120V grid, Maximum **6** units SG800 Microinverters per branch.
2. The max DC input power of each inverter is **800W** (the PV module max output power is  $4 \times 200W / 2 \times 400$ ).
3. The **VOC** of PV modules should not be greater than the max DC input voltage of Microinverters.

SG800 Series Microinverter

@

2-Phase 208/240V(Single-Phase 120V)




1. SG800 Series @2-Phase 208/240V grid, Maximum **11** units SG800 Microinverters per branch.
2. The max DC input power of each inverter is **800W** (the PV module max output power is  $4 \times 200W / 2 \times 400$ ).
3. The **VOC** of PV modules should not be greater than the max DC input voltage of Microinverters.

SG800 Series Microinverter

@

Single-Phase 230V



1. SG800 Series @Single-Phase 230V grid, Maximum **11** units SG800 Microinverters per branch.
2. The max DC input power of each inverter is **800W** (the PV module max output power is  $4 \times 200W / 2 \times 400$ ).
3. The **VOC** of PV modules should not be greater than the max DC input voltage of Microinverters.


# Wiring Schematic

SG800 Series Microinverter

@

Single-Phase 230V

Micro Inverter Voltage	120/230VAC
Grid Voltage	230V
Grid Type	Single Phase




SG800 Series Microinverter

@

Single-Phase 120V

Micro Inverter Voltage	120/230VAC
Grid Voltage	120V
Grid Type	Single Phase




## SG800 Series Microinverter



## 2-Phase 208/240V(Single-Phase 120V)

Micro Inverter Voltage	120/230VAC
Grid Voltage	208/240V
Grid Type	Dual Phase




## SG800 Series Microinverter



## 3-Phase 380V(Single-Phase 230V)

Micro Inverter Voltage	120/230VAC
Grid Voltage	380V
Grid Type	Triple Phase




# SG800 Series Microinverter



# 3-Phase 208/240V(Single-Phase 120V) I

Micro Inverter Voltage	120/230VAC
Grid Voltage	208/240V
Grid Type	Triple Phase



# SG800 Series Microinverter



# 3-Phase 208/240V(Single-Phase 120V) II

Micro Inverter Voltage	120/230VAC
Grid Voltage	208/240V
Grid Type	Triple Phase

