



LOW COST - NO LEAKS - QUICK INSTALL

KB Racking's **BARNRACK** solar mounting system is designed for all corrugated metal rooftops. The system is specially engineered for quick and easy installation, at a cost effective price for large systems.

BARNRACK is made of lightweight aluminum components for minimal additional load on the roof. The system includes two sealant layers for extra prevention against leaks. It is designed to run parallel to the roof seams while allowing ample room for ventilation to ensure optimal power output.

H

FEATURES

- BARNRACK hooks customized to every roof profile
- Fast installation: up to 1kW/ man-hour
- Light, corrosion-free aluminum components
- Optimized ventilation gap cools panels for higher power output
- Doubled sealed hooks with factory applied rubber sealant
- Roof penetrated only once per bracket for greater protection against leaks
- 10-year standard product warranty, extended warranty available









TECHNICAL

SPECIFICATIONS

Distribution Load	2 - 3 lbs/ft ²
Inclinations	0°-10°
Wind Speed	Up to 100mph for Exposure B
Material	High grade aluminum and stainless steel
Panel Type	All standard size framed PV modules
Orientation	Landscape and portrait
Rail Length	Up to 20' (6.2m)
Ventilation Spacing	3.9" (10 cm) between panel and roof
Roof Pitch	5° - 80°
Roof Type	Corrugated sheet metal
Grounding Method	ETL certified grounding clamps
ETL Certification	Entire system certified for 0° inclination
Module Spacing	Customizable between 64-106" (1.63-2.7m)
	0.8" (2cm) spacing module-module
	3.9*(10cm) C°-10* Boof Pitch: 3°-25*

MADE IN AMERICA



MADE IN CANADA

www.kbracking.com • 1.888.661.3204 • info@kbracking.com