

Greenhouse specification				
Size:	Span Width(m)	8m, 9m, 9.6m	Hot selling multi span models: 32x16m, 32x32m, 40x16m, 40x32m, 40x40m, 40x48m, 48x48m,60x64m, 64x64m, 100x96m, 100x104m.  <b>All parameters are for reference only. Every size and dimension details can be customized.</b>	
	Arch Span(m)	3m, 4m, 5m		
	Gutter Height(m)	3m, 4m, 5m		
	Top Height(m)	5-7.5m		
Steel Structure	Material	Round, Rectangular, Square, Arch tube, Gutter		
	Size	Round: $\phi 25 \times 1.2(1.5), \phi 30 \times 1.2(1.5), \phi 42 \times 1.2(1.5), \phi 60 \times 1.2(1.5), \phi 90 \times 2.5(3.8)$ Rectangular: 20*40*1.5(2.0), 50*80*1.5(2.0), 50*100*1.5(2.0), 80*120*2.0(2.5) Square: 30*30*1.5, 50*50*1.5(2.5), 80*80*2.0(3.0), 120*120*2.5(5.0) Gutter: 1.5 (thickness), 1.4m (length) <b>(All main parts are hot dipping galvanized after processing with zinc cover 275G/M2)</b>		
	Life Span	10 years		
Covering	Material	Greece PE film	Polycarbonate(PC) sheet	Glass
	Thickness	200/150 micro 3-layers extruding film	8mm/6mm for double wall	4mm(tempering glass)
	Size	Custom sizes available	the width maximum 2.1m	the width maximum: 1m, 1.5m
	Life Span	3-5	8-10	15-20
	Features	1) Temperature range: -40°C to +60°C. 2) UV Resistant, Anti-aging, Anti-Mildew, Anti-drip, etc. 3) 80% light transmission	1) Can be easily cut in any pattern using a circular saw with a fine tooth blade. 2) Weight is about 11.2kg/m2. 3) 85% light transmission	1) Weight is about 10kg/m2. 2) 90% light transmission
Air Vent	Two Sides Vents(film roller), Roof Ventilation <b>(manual or automative operation)</b>			
Spare Parts	All anchor, bolt, clamp element and other parts are included in pack.			
Assembly	4 person use 7days to install 1 set 1000m2 with installation guide			
Climate Resistance	Snow load: 0.35KN/M2, Wind Load: 120-140km/h, Rainfall: 140mm/h, Crops hanging load: 15-25kg/m2			